

COUNTY	LEA	FIELD	Vacuum-Yates	STATE	N.M.
OPR	PHILLIPS PETROLEUM COMPANY				MAP
97 Santa Fe					
Sec. 33, T-17-S, R-35-E					CO-ORD
990' fr S Line & 1980' fr W Line of Sec.					
Spud 5-21-64				CLASS	EL 39572
Comp 6-23-64				FORMATION	DATUM
CSG & SX - TUBING				LOG:	
8 5/8" 1624' 650				Yates 2898	
4 1/2" 6300' 800				Queen 3775	
				Gryb 4068	
				SA 4464	
				Glor 6038	2081
LOGS EL GR RA IND HC A					
				TD 6300', PBD 3294'	

IP Yates Perfs 3082-3104' Flwd 39 BOPD, (On Intermittent). Pot.
Based on 24 hr test thru 24/64" chk., TP 500-100#, gravity
33.2, GOR 1590.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Co. Tools	PROP DEPTH	6400'	TYPE
DATE				

F.R. 5-21-64
PD 6400' - Paddock
Contractor - Co. Tools

5-25-64 Drlg. 3356'.
6-1-64 Drlg. 5404'.
6-8-64 TD 6300', WOC.
6-15-64 TD 6300', PBD 6255', prep to Re-Ac.
Perf 6192-6208' W/2 SPF
Ac. 1000 gals.
Swbd 4 BO + 64 B Salt wtr in 9 hrs.
Squeezed perfs 6192-6208' W/75 sx.
Perf 6174-84' W/2 SPF
Ac. 500 gals.
Swbd 90 BLO, 12 BAW, 4 BNO & 6 BFW/8 hrs.

6-22-64 TD 6300', PBD 3294', flowing load.
Swbd 4 BO + 18 B Salt Wtr in 3 hrs from 6174-84'.
Re-Ac. 2000 gals. 6174-84'.
Swbd 3 BO + 38 B Salt Wtr in 3½ hrs
Ran Tracer; indicated fluid entry from perfs.
Set BP @ 6100' & 3300'.

6-22-64 - cont'd -

Perf (Yates) 3082-90' & 3094-3104' W/2 SPF
Ac. 1000 gals.

Swbd dry, w/small show of gas.

Frac 20,000 gals oil + 30,000# sd.

Flwd 506 BLO/24 hrs thru 1/2" chk., TP 100#,
CP 300#. (-100 BLO).

6-29-64 TD 6300', PBD 3294', COMPLETED.