

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NE MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No. B1501	
7. Unit Agreement Name	
8. Farm or Lease Name Santa Fe	
9. Well No. 100	
10. Field and Pool, or Wildcat Vacuum Glorieta	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator Phillips Petroleum Company
3. Address of Operator Room 711, Phillips Bldg., Odessa, Texas 79761
4. Location of Well UNIT LETTER <u>0</u> <u>819</u> FEET FROM THE <u>south</u> LINE AND <u>1955</u> FEET FROM THE <u>east</u> LINE, SECTION <u>30</u> TOWNSHIP <u>17-S</u> RANGE <u>35-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3994' RKB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUS AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-22-75: MI Well Units rig, pld rods and pump
9-23-75: Ran 2-3/8" tbg w/baker R pkr, set at 6000'. Unable to load annulus, pkr failed.
Pld tbg & pkr.
9-24-75: Set 2-3/8" tbg w/Baker R pkr at 6000'. B-J treated down tbg thru csg perfs 6064-74'
w/2000 gals 28% NE HCL acid & 2000 gals 3% NE HCL acid. Flushed w/24 BW. Max press
2000#, min press 9", AIR 4 BPM. Swbd 6-1/2 hrs, 52 BO, 60 FAW & LW.
9-25-75: Pld tbg & pkr. Set 2-3/8" tbg at 6044' w/Baker anchor on bottom. Set 2"x1-1/4"x16'
pump at 6041'. Released unit. P/12 hrs, no gauge.
9-26-75: P/24 hrs, 82 BO, 60 BLW.
9-27-75: P/24 hrs, 75 BO, 32 BSW.
9-28-75: P/24 hrs, 68 BO, 24 BSW.
9-29-75: P/24 hrs, 63 BO, 9 BSW.
9-30-75: P/24 hrs, 82 BO, no water, GOR 838/1, gty 38.6, f/perfs 6064-74'. Restored to production.
Series 900 BOP, 3000# WP, double w/one set pipe rams and one set blind rams, manually operated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed <u>W. J. Mueller</u>	TITLE <u>Engineering Advisor</u>	DATE <u>10-1-75</u>
Orig. Signed by <u>John Runyan</u>	TITLE <u>Geologist</u>	DATE <u>10/1/75</u>
APPROVED BY	TITLE	DATE

CONDITIONS OF APPROVAL, IF ANY: