

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from surface feet to 6225' TD feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing September 21, 1964
OIL WELL: The production during the first 24 hours was 291 barrels of liquid of which 99% was oil; % was emulsion; % water; and 1% was sediment. A.P.I. Gravity 37.9
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	1583	T. Devonian	T. Ojo Alamo
T. Salt		T. Silurian	T. Kirtland-Fruitland
B. Salt		T. Montoya	T. Farmington
T. Yates	2890	T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen	3750	T. Ellenburger	T. Point Lookout
T. Grayburg	4014	T. Gr. Wash.	T. Mancos
T. San Andres	4485	T. Granite	T. Dakota
T. Glorieta	5974	T.	T. Morrison
T. Drinkard		T.	T. Penn.
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn.		T.	T.
T. Miss.		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	849	849	Redbed				
849	3673	2824	Redbed, anhydrite				
3673	4025	352	Anhydrite, lime				
4025	6225	2200	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 22, 1964
Company or Operator Phillips Petroleum Company Address Box 2130 - Hobbs, New Mexico
Name M. G. Croston Position or Title Office Manager