

|                                          |                               |                     |                |           |       |
|------------------------------------------|-------------------------------|---------------------|----------------|-----------|-------|
| COUNTY                                   | LEA                           | FIELD               | Vacuum-Paddock | STATE     | NM.   |
| OPR                                      | STANDARD OIL COMPANY OF TEXAS |                     |                |           | MAP   |
| 10 State "4-27"                          |                               |                     |                |           |       |
| Sec. 27, T-17-S, R-35-E                  |                               |                     |                | CO-ORD    |       |
| 1650' fr S Line & 330' fr W Line of Sec. |                               |                     |                |           |       |
| Spud 4-26-64                             |                               | CLASS               |                |           |       |
| Comp 5-24-64                             |                               | EL 3946             |                |           |       |
|                                          |                               | FORMATION           | DATUM          | FORMATION | DATUM |
| CSG & SX - TUBING                        |                               | LOG:                |                |           |       |
| 5/8" 1602' 950                           |                               | Yates 2858          |                |           |       |
| 4 1/2" 6262' 870                         |                               | 7-R 3022            |                |           |       |
|                                          |                               | Queen 3685          |                |           |       |
|                                          |                               | SA 4300             |                |           |       |
|                                          |                               | Glor 5954           |                |           |       |
| LOGS EL GR RA IND HC A                   |                               | Padd 6031           |                |           |       |
|                                          |                               | TD 6268', PBD 6224' |                |           |       |

IP Paddock Perfs 6102-38' Flwd 75 BOPD. Pot. Based on 24 hr  
st thru 1/8" chk., TP 350#, gravity 38., GOR 685.

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|                       |                  |      |
|-----------------------|------------------|------|
| CONT. Noble Drlg. Co. | PROP DEPTH 6350' | TYPE |
| DATE                  |                  |      |

F.R. 4-30-64

PD 6350' - Paddock

Contractor - Noble Drlg. Co.

4-28-64 Drlg. 300'.

4-64 Drlg. 3000'.

5-11-64 Drlg. 6000' sd. & sh.

5-12-64 TD 6147', reaming.

Cored 6032-58', rec 24' anhy. dolo., w/fracs.,  
scatt. poro. & show.

Cored 6058-70', rec 12' anhy. dolo., w/fracs.,  
good poro. & show.

Cored 6070-96', rec 26' anhy. dolo., w/fracs., good  
poro. & show.

Cored 6096-6147', rec 51' same.

5-18-64 TD 6268', WOC.

Cored 6147-6190', rec 43' dolo., w/scatt. vuggs,  
bldg. oil & wtr.

5-5-64 TD 6268', PBD 6224', WO Potential.

5-25-64 -cont.-  
Perf 6102-24' & 6132-38' W/1 SPF  
Flwd 60 BLO + 52 BNO/9 hrs.  
6-1-64 TD 6268', PBD 6224', COMPLETED.