	State 5-27	ddress <b>Drawer "S"</b> Tell No. 5	Section 27 54178;
	RECORD	OF INCLINATION	
D	Angle of		Accumulative
Depth (feet)	Inclination (degree		
880	1/4	1.83 8.03	1,83 9.86
1200	1/2	2.79	12.65
1450	3/4	3.27	15.92
<u>1510</u>	1/2	1.40	17.32
2350	<u>3/4</u>	3.80 1.96	<u>21.12</u> 23.08
2700	1	6.11	29.19
<u>2915</u> 3160	3/4	2.81	32.00
3670	3 -	26.69	<u> 32.00</u> 58.69
3940	2-1/4	10.60	69.29
4120	1/2	1.57	70.86
<u> 4233</u> 4500	1/2	2.33	71.85 74.18
4750	3/4	3.27	77.45
<u> 5204</u>	2-1/2	19.80	97.25
5507 5770	3-3/4	23.77 17.20	121.02
5990	3-1/2	10.99	138.22 149.21
6200	3-1/4	14.17	163.38
6268 T.D.	3-3/4	4.45	167.83
		Total Displac	ement 167.83
Was survey run in Tubi Distance to nearest le Distance to lease line Certification of person	ase line 530 fees as prescribed by fie	ion Data:	
form, and that such in	y that I have personal formation given above	knowledge of the data a is true and complete.	nd facts placed on this
		Signature	MILLEY TO THE TOTAL TO THE TOTAL TOT
		_	
		NOBLE DRILLING	CORPORATION
		Company	
Operator Affidavit:			
		ses, and must file explanatory stat	tement when applicable.)
KILOWIL to me to be the person u	authority, on this day, personallyhose name is subscribed hereto		,
identified in this instrument), and	d that such well was not intent	ing at the direction and on behalf of	
mendagagagagagagagaga	SCORECTOR DESCRIPTION OF THE INTERNATION OF THE INT	was the vertical w	hatsoever. (
		39/ Evening	Lead Engineer
		Signature and Tit	tle of Affiant
Sworn and Subscrib	ed to before me, this	the 5th day of	
		Glorae C	Law linns
		Notary Public in	and for Ward

County, Texas.

## II. INCLINATION SURVEYS

## A. Requirement of

- l. An inclination survey made by persons or concerns approved by the Commission shall be filed on a form prescribed by the Commission for each well drilled or deepened with rotary tools or when as a result of any operation the course of the well is changed.
- a. The first shot point of such inclination survey shall be made at a depth not greater than 500 feet below the surface of the ground and succeeding shot points shall be made either at 500 foot intervals or at the nearest drill bit change thereto; but not to exceed 1000 feet apart.
- 2. Inclination surveys conforming to these requirements may be made either during the normal course of drilling or after the well has reached total depth. Acceptable directional surveys may be filed in lieu of inclination surveys.
- 3. Copies of all directional or inclination surveys, regardless of the reason for which they are run, shall be filed as a part of or in addition to the inclination surveys otherwise required by this rule.

## B. Reports

- 1. The report form prescribed by the Commission shall require that it be signed and certified by a party having personal knowledge of the facts therein contained.
- a. The report shall include a tabulation of the maximum drifts which could occur between the surface and the first shot point and each two successive shot points, assuming that all of the unsurveyed hole between any two shot points has the same inclination as that measured at the lowest shot point, and the total possible accumulative drift, assuming that all measured angles of inclination are in the same direction.
- 2. In addition, the report shall be accompanied by a sworn statement of the operator, or of someone acting at his direction on his behalf either, (1) that the well was not intentionally deviated from vertical whatsoever or, (2) that the well was deviated at random, with an explanation of the circumstances.
- 3. The report shall be filed in the District Office of the Commission for the district in which the well is drilled, by attaching one copy to each appropriate completion form for the well.
- 4. The Commission may require the submittal of the original charts, graphs, or discs resulting from the surveys.