

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1839

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Chevron U.S.A. Inc.

Address of Operator
P. O. Box 1660, Midland, Texas 79702

Location of Well

UNIT LETTER D 990 FEET FROM THE north LINE AND 330 FEET FROM
THE west LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
State 5-27

9. Well No.
8

10. Field and Pool, or Wildcat
Vacuum (Glorieta)

15. Elevation (Show whether DF, RT, GR, etc.)
KB 3947'; GR 3935'

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
REPAIR OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set RBP @ 5700 & spot 2 sxs sand on top. Press to 1000 psi - ok. Perfd 4 holes @ 1700. Circ down tbg & out 4-1/2" x8-5/8" ann. Ran cmt rtnr & set @ 1649, tstd tbg & ann to 1000 psi. Mix & pmp 600 sxs class "C" cmt, yield 1.32;14.8 ppg. Pmp 100 sxs class "C" cmt w/2% cacl; yield 1.32, 14.8 ppg. Circ 250 sxs cmt to surf. Displace w/FW. RIH w/bit & DOC 1644-1649, rtnr @ 1649 & cmt fr 1656-1761. Circ & press to 500 psi - ok. RIH & wash sand off RBP. Displace hole w/100 bbls 2% KCL wtr & POOH w/tbg & RBP. RIH w/2-3/8" prod tbg, mud anchor, PSN & tbg anchor, tstg to 5000 psi. LDD tbg @ 6117, ran R & P & return well to production.

Work commenced on 8-26-81

Work completed on 8-31 81

Production prior: Pump 15 BO, 64 BW & 8Mcfgpd.

Production after: Pump 15 BO, 90 BW & 9Mcfgpd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. R. Graham TITLE Engineering Technologist DATE May 26, 1982

ORIGINAL SIGNED BY

APPROVED BY JERRY SEXTON

TITLE

DATE JUN 1 1982

CONDITIONS OF APPROVAL, IF ANY: