i				
	etj	on	12	
		-	1	Ŷ
				Ŷ.
				ŝ

## NEW MEXICO OIL CONSERVATION COMMISSION

OIL CONSERVATION CO. C. C. Santa Fe. New Mexico WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Well No	7	<b>II</b>	W of	1/ of \$cc	32	. 17 South _	35 Bast NMPM
Well No		Clorieta)					
Well is							County
of Section							lin
			_				er 8 , 19 64
							, 19.09
							o be kept confidential unti
Not Co	mfidentia	1	, 19			A STACE OF THE PARTY OF THE PAR	o be kept confidential unti
				OT 343777 OD 1		•	
No. 1 forms	60	76	6180	OIL SANDS OR 2		**	
No. 1, from							
No. 3, Irom	· ····································	t/	O	No.	6, from	to.	
			IMI	PORTANT WATE	R SANDS		
Include data	a on rate of wa	ter inflow and	elevation to wh	ich water rose in ho	ole.		
No. 1, from	_		to	••••		feet	
		loca				_	
No. 2, from		lone	to			feet.	
No. 2, from		licoa	toto			feet.	
No. 2, from		licoa	toto			feet.	
No. 2, from No. 3, from No. 4, from	WEIGH	I NEW	to	CASING RECO	ORD	fort.	
No. 2, from	WEIGH PER PO	r New	to	CASING RECO	)RD	fort.	
No. 2, from No. 3, from No. 4, from	WEIGH	r NEW USE	to	CASING BECO	ORD  CUT AND PULLED FRO	feet.  feet.  feet.  perforations	PURPOSE Surface Strik
No. 2, from No. 3, from No. 4, from	WEIGH PER FOO	r NEW USE	to	CASING RECO	ORD  CUT AND PULLED FRO	fort.	
No. 2, from No. 3, from No. 4, from	WEIGH PER FOO	r NEW USE	to	CASING BECO	ORD  CUT AND PULLED FRO	feet.  feet.  feet.  perforations	PURPOSE Surface Strik
No. 2, from No. 3, from No. 4, from	WEIGH PER FOO	r NEW USE	OR AMOUS	CASING BECO	ORD  OUT AND PULLED FRO  Hone  Frome	feet.  feet.  feet.  pebforations  6080-6158	PURPOSE Surface Strik
No. 2, from No. 3, from No. 4, from	WEIGH PER FOO	r NEW USE	OR AMOU?  Sew 1584  6236  MUDDII	CASING RECO	ORD  OUT AND PULLED FRO  Hone  Frome	feet.  MED  MUD	PURPOSE  Surface String  611 String
No. 2, from No. 3, from No. 4, from  SIZE  5/8* 1/2*  SIZE OF	WEIGH PER POOL	NEW USE	OR AMOU?  Sey 158  MUDDI  NO. SACKS OF CEMENT	CASING BECO  KIND OF SHOE  Float  NG AND CEMENT  METHOD USED	CUT AND PULLED FRO	feet.  feet.  feet.  feet.  feet.  feet.  6080-6158	PURPOSE  Surface String  11 String
No. 2, from No. 3, from No. 4, from  SIZE  5/8* 1/2*  SIZE OF	WEIGH PER PO	NEW USE	OR AMOU?  Sew 1584  6236  MUDDII	CASING RECO	ORD  CUT AND PULLED FRO  Rone  Rone  Rone  Fine	feet.  MED  MUD	PURPOSE  Surface String  611 String

Depth Cleaned Out.

## RECORD OF DRILL-STEM AND SPECIAL

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

,	is were us	ed from								feet.
Cable tools	were use	d from	feet to	o	••••••	feet, and	l from		feet to	feet.
					RODUC	rion				
out to Pro			September 12	•						
OIL WEL	L: The	production	during the first 24 hou	urs was	6	3	barr	els of liqu	uid of which	100 % was
	was	oil;	■	mulsion;'	<b>+=</b>		% water;	and	%	was sediment. A.P.I.
	Grav	vi <b>tv</b> ≎	39.7 degrees					:		
GAS WEL		•	during the first 24 hor				I.C.F. plu	S		barrels of
JAS WEL										
	•	•	rbon. Shut in Pressure							
							·.			
PLEA	SE IND	ICATE BE	LOW FORMATION Southeastern New M		CONF	DRMANC	E WITH	GEOGR		New Mexico
т 4-1	1	histler	1523' (+2456't)					Т.	3.1	
-			T.	Silurian		•••••			=	d
		1 27		Montoya.					Farmington	•••••
Γ. Yates.	•••••	25	45' (+1134') T	Simpson				т.	Pictured Cliffs	
Γ. <b>7 Riv</b> e	ers	30	14' (+ 965') <sub>T.</sub>	McKee					the second secon	***************************************
T. Queer	n		03' (+ 276') <sub>T.</sub>	Ellenburg	ger		······································	Т.	Point Lookout	
Γ. Grayb	ourg		55' (+ SA') <sub>T</sub> .							
I'. San A	Andres		00' (- 321') <sub>T.</sub>	Granite						
T. Glorie	eta		64' (-1985') <sub>T.</sub>					_		
Т. жи		Mock 60					,			
			Т.	***************************************				_		
			Т.				••••••	1.	***************************************	
			т					т.		
T Miss			T.							•••••
T. Miss			T.							•••••
T. Miss.			Т.	FORM		RECO	RD	Thicknes	3 70	
T. Miss				FORM				т.	3 70	•••••
From		Thickness in Feet	Т.	FORM		RECO	RD	Thicknes	3 70	
From 300 '	To 6050' 6130'	Thickness in Feet	Formati	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 300 '	To 6050' 6130'	Thickness in Feet	Formati	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	
From 900'	To 6050' 6130' 6150'	Thickness in Feet  250° 80° 20°	Formati Ls, dolo. Ls, dolo & se Ls, dolo.	FORM		RECO	RD	Thicknes	3 70	

I hereby swear or affirm that the information given herewith is a	complete and correct record of the well and all work done on it so far
as can be determined from available records.	September 16, 196
Standard Oil Company of Texas, A Company of Operato Bivision of California Oil Company Name A. L. Clefander R. L. Alexander	(Date)
Company of Operato Division of California	and dress. Brainer B. Bonana ha his a warmen
Name T. L. Clefander R. L. Alexander	Position or Title