

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 300-25-20945
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-155-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
TEXACO E & P INC.

3. Address of Operator
PO BOX 3109; MIDLAND, TEXAS 79701

7. Lease Name or Unit Agreement Name
NEW MEXICO "O" STATE NCT-1

8. Well No.
16

9. Pool name or Wildcat
VACUUM GLORIETA/BLINEBRY

4. Well Location
Unit Letter H : 1980 Feet From The NORTH Line and 990 Feet From The EAST Line

Section 36 Township 17S Range 34E NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4002 (DF)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) NOTIFY NMOC D OF INTENT TO PLUG AND ABANDON.
- 2) NOTE THIS IS A DUAL COMPLETION WELL W/ 2 STRINGS OF 2 7/8" CSG USED AS CSG.
- 3) TIH W/ 2 1/16" TUB ON Y-SIDE (GLORIETA) CIRC CSG W/ 25# PER BBL. SALT GEL MUD.
- 4) TDH W/ 2 1/16" TUB RIG UP WIRELINE & SET CMT RETAINER @ 6150'
- 5) SQZ PERF 6200'-6205' W/ 60 SX CMT. UNSTING F/ RETAINER & CAP W/ 100' OF CMT F/ 6150'-6050'. (Y-SIDE)
- 6) SPOT 10 SX CMT F/ 4390'-4190' (TOP SAN ANDRES 4340') (Y-SIDE)
- 7) SPOT 10 SX CMT F/ 3735'-3435' (TOP QUEENS 3685') (Y-SIDE)
- 8) PERF @ 3350' & SQZ 35 SX CMT W/ CMT RETAINER @ 3300'. (8 5/8" SHOE @ 3300')
- 9) SPOT 10 SX CMT F/ 3300'-3000'
- 10) PERF @ 2828' & SQZ 35 SX CMT W/ CMT RETAINER @ 2800'. (TOP OF YATES 2778')
- 11) SPOT 15 SX 2800'-2390'. (B-SALT 2640')
- 12) SPOT 10 SX 1650'-1350'. (B-SALT 1596' 113/4" CSG SHOE @ 1530')

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R.J. Harding III TITLE OPERATIONS ENGINEER DATE 9/15/68
TYPE OR PRINT NAME R.J. HARDING III TELEPHONE NO. 915/688/4816

(This space not to be used)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

- 13) PERF @ 260' & CIRC CMT TO SURFACE @ 120 SX CMT. (Y-SIDE IS PLUGGED)
14) RIG UPON Z-SIDE (BLINE BRY) TIH W/ CMT RETAINER @ 6000' & SQZ PERF @ 6167'-6180'
W/ 45 SX CMT. UNSTING & CAP W/ 100' OF CMT F/ 6000'-5900'. CIRC CSG W/ 25# PER BBL.
SALT GEL MUD.
15) SPOT 10 SX CMT F/ 4390'-4190' (TOP S-ANDRES 4340')
16) SPOT 10 SX CMT F/ 3735'-3435' (TOP QUEENS 3685')
17) SPOT 10 SX CMT F/ 3350'-3050' (8 5/8" CSG SHOE 3300')
18) SPOT 10 SX CMT F/ 2828'-2528' (TOP YATES 2778')
19) SPOT 10 SX CMT F/ 1650'-1350' (TOP SALT 1596' 11 3/4" CSG SHOE @ 1530')
20) SPOT 10 SX CMT F/ 260'-SURFACE (Z-SIDE PLUGGED)
21) NIPPLE DOWN BOP & CUT OFF WELL HEAD; CAP WELL; INSTALL DRY HOLE MARKER
22) CLEAN UP LOCATION RIG DOWN & MOVE OFF.

RECEIVED

1995

TEXACO
NM O STATE NCT-1 NO. 16
API# 30025209450000

PROPOSED

- Y - Z -

10sx 260' - 0

0 - 1530' Cement 1000 sx
Perf @ 260' & circ cmt to surface
@ 1205x5 cmt

0 - 1530' 15" OD Openhole

Spot 10sx - 1650' - 1350' (TSA) 21596)

0 - 1530' 11.75" OD Surface Casing

Spot 15sx. 2800 - 2390 (B-SAN) 2640)

0 - 3300' Cement 750 sx

1530 - 3300' 10.625" OD Openhole
Perf @ 2828' & SQZ 35sx w/circ
@ 2800'

Perf @ 3350' & SQZ 35sx w/circ @ 3300'
3292 - 6800' Cement 1200 sx (CBL)

0 - 3300' 8.625" OD Intermediate Casing

Spot 10sx. - 3735 - 3435
Top Queens 3685'

3300 - 6800' 7.875" OD Openhole

10sx. 4390' - 4190' (T-SAN, 4340')

Y-side circ @ 6150' & SQZ.
60sx. cmt into Perf @ 6200' - 6205'
unstringing & cap w/ 100' of cmt.

6200 - 6205' Perfs (COMMUNICATE STRINGS)

6650 - 6660' CIBP

6680 - 6759' Abandoned Perfs

0 - 6800' 2.875" OD Tubing

0 - 6797' 2.875" OD Tubing

Y-side GLORIETA

Z - BLINEBRY

Spot 10sx cmt f/ 260' - surface. (Z-side)

- 260'

- 1530'
Spot 10sx cmt f/ 1650' - 1350' (Z-side)

NO cmt @ 3292' - 1530' (Z-side)
by BOND Log Behind 2 7/8" csg.

Spot 10sx. cmt f/ 2828' - 2528' (Z-side)

- 3300'
10sx. cmt f/ 3350' - 3050' (Z-side)

Spot 10sx. f/ 3735' - 3435' (Z-side)

10sx. cmt f/ 4390' - 4190' (Z-side)

circ @ 6000' & SQZ perf @ 6167' - 6180' w/ 45sx. cmt.
unstringing & cap w/ 100' cmt.

6029 - 6061' SQZ Perfs (SQZ w/ 240 sx)
6167 - 6180' Perfs.

- CIBP @ Z-side @ 6650'

Y - Z -
TD: 6800'

TEXACO
NM O STATE NCT-1 NO. 16
API# 30025209450000

