

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-025-20334 20951

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-1030-1

7. Lease Name or Unit Agreement Name:

Vacuum Glorieta
West Unit

8. Well No.

25

9. Pool name or Wildcat

Vacuum Glorieta

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Texaco Exploration & Production, , Inc.

3. Address of Operator

P. O. Box 3109, Midland, TX 79702

4. Well Location

Unit Letter H : 1965 feet from the FNL line and 865 feet from the FEL line

Section 25 Township 17S Range 34E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Set 2 7/8" CIBP @ 6000', (Glorieta) Fill 2 7/8" Csg w/80 Sx plug 6000'-2800' WOC Tag
2. Perf 6 holes @ 2800', Sqz 50 Sx plug 2800'-2600' (Yates, B-Salt)
3. Perf 6 holes @ 1700', Sqz 50 Sx plug 1700'-1500' (8 5/8 Shoe, T-Salt) WOC Tag
4. Fill 2 7/8" Csg w/35 Sx plug 1500'-Surf
5. Install dry hole marker.
- * Perf @ 1648', sqz 725 Sx Cmt, no records of Cmt Circ.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James T. Corbett TITLE FACULTY ENGINEER DATE 8/1/01

Type or print name JAMES T. CORBITT Telephone No. 915 688-4438

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

5
C

MP