

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 11-1-73

0+6-NMOCD-Hobbs 1-Mr. J.A. Midland
1-File 1-Laura Richardson-Midland
1-Engr LM 1-JA, 1-BB
1-Foreman EF 1-CB, 1-CP

State ☒ Encl ☐	
5. State Oil & Gas Lease No. B-1565	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER: NIO oil Well		7. Unit Agreement Name
2. Name of Operator Getty Oil Company		8. Farm or Lease Name State BC
3. Address of Operator P.O. Box 730, Hobbs, NM 88240		9. Well No. 3
4. Location of Well UNIT LETTER M 990 FEET FROM THE South LINE AND 330 FEET FROM West LINE, SECTION 33 TOWNSHIP 17S RANGE 35E N.M.P.M.		10. Field and Pool, or Wildcat Vacuum Glorieta
15. Elevation (Show whether DF, RT, GR, etc.) 3962' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/15/83 4 1/2" @ 6316', top cement 1600', 7 5/8" @ 1583' circ. cmt. BP @ 6115', perfs 6005-6095. Move in rig up.
12/16/83 Ran 3 7/8" bit & csg. scraper to 6013'. Pull bit, set CI plug on tbq @ 5977', circ. hole w/ salt gel mud spot 35' - 2 1/2" sxs cement, pull tbq to 4312'. Set 25 sxs cement back to 3952'.
12/17/83 By Western spot 25 sxs class "C" 4312-3952'. Spot 25 sxs "C" 1963-1609'. CRC perfed 4 1/2" csg @ 1450', 2 holes, cement thru perfs w/ 250 sxs class "C" circ. 15 sxs displace cement 20' from surface.
12/19/83 Nipple down wellhead. Install dry hole marker. Rig down Baber. P&A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Donald E. Steiner TITLE Area Superintendent DATE December 21, 1983

Signed Dale R. Crockett TITLE Oil & Gas Inspector DATE AUG 27 1985

APPROVED BY Ronald M. Crockett TITLE OIL & GAS INSPECTOR DATE AUG 27 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
DEC 22 1983
D.C.D.
HOBBS OFFICE