N.									
							χ		
		•							

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

HOBBS OFFICE O. C. C.

WELL RECORD MAY 2/ 10 28 AM 64

MAIL TO DISTRICT OFFICE, OIL CONSERVATION COMMISSION, TO WHICH FORM

HUMBLE	OIL & RI	EFINING	COMPAN	Y	New	Mexico Stat	e K		
	. (C	OMPANY OR	DPIRATO	U N	tr	20	(LEASE)) F T
ELL NO.	mat ad	, IN Voor	35	% OF	¼, OF \$	SEC	_, T. 17-8	, R	35-E , NMI
maesig	naceu -	vacuum (noriet	a (1)	POOL,		<u>Lea</u>		COUN
ELL IS	1865	FEET	FROM	North	LINE AN	D330	FEET FI	ROM	East [
F SECTIO	ON024		. IF STA	TE LAND TH	IE OIL AND G	AS LEASE NO.	ISA-132	50	
RILLING	COMMENC	ED	ipril 3	0	_, 19 <u>.64</u> DRII	LLING WAS CO	MPLETED	May	<u>, 13, 19(</u>
AME OF	DRILLING	CONTRAC	TOR	· .	Sharp D	rilling Com	pany	·	
DURESS_			.		Midland	Texas			
				OF TUBING	HEAD 3955	D. F.	THE INFO	RMATIO	N GIVEN IS TO
	FIDENTIAL FROM RDI		- HEAD	FLANGE	13.50	19 DA	TE WELL CO	MPLETEI	0 <u>5-19-64</u>
			·	OIL	SANDS OR	ZONES			
). 1, FR	OM 60	076.	TO	6084	NO	. 4, FROM	·	TO	
O. 2, FR	OM	<u> </u>			NO	. 5, FROM	 	TO	
O. 3, FR	OM					. 6, FROM			
•	•	•		IMPO	RTANT WAT	FR SANDS		٠	
CLUDE I	DATA ON F	ATE OF W	VATER IN			O WHICH WA	TER ROSE IN H	IOLE.	
		•					•		
). 2, FR	DM			TO	`				
). 3, FR(DM			TO			FEET.		
). 4, FR	DM	·		TO			FEET		
					CASING REC				
SIZE	WEIGI	HT N	EW OR		KIND OF	CUT AND			
	PER FO	ООТ	USED	AMOUNT	SHOE	PULLED FROM	PERFORATIO	NS	PURPOSE
3-5/8 - }	9.5&1		<u>New</u> New	1537 6197	Baker Baker	-	(OT/ (OT/		Surface
				<u> </u>	Dakel		6076-6084		Oil String
									,
			M	UDDING	AND CEMEN	NTING RECO	RD		
SIZE OF	SIZE OF	WHERE		O. SACKS	METHOD		MUD		OP OF CEMEN
HOLE -1/4	8-5/8		SET OF CEMENT USED			GRAVITY			
-7/8	4-1/2	1552 6210			Pumped Pumped			Cement circulated 2800 by temp. surve	
								2000 1	by temp. sur
 -		· · · · · · · · · · · · · · · · · · ·							
		•	RECOR	D OF PR	ODUCTION .	AND STIMUL	ATION		
•	(REC	ORD THE	PROČESS	USED, NO.	OF QTS. OR G	ALS. USED, INT	ERVAL TREATE	D OR SH	OT.)
otted	500 gals	. acetic	acid	on botto	m. Displac	ed water in	casing wi	th oil.	Spotted
7 77 6	acetic	acid or	botto	m. Swab	bed well dr	y. Perf. L	lu casing	from 60	076 to 6084
u gara	o active	jet sho	ot per	ft. Aci	dized above	perf. with	the above	500 ga	ls. acetic
e radi								- 0	'
radi						nmaes 3100	4 100	D	1350 #. (Coi