

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1839	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐
Name of Operator		
Chevron U.S.A. Inc.		
Address of Operator		
P. O. Box 1660, Midland, Texas 79702		
Location of Well		
UNIT LETTER	C	990
		north
		2173
FEET FROM THE LINE AND FEET FROM		
THE	west	LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
State 5-27
9. Well No.
7
10. Field and Pool, or Wildcat
Vacuum (Glorieta)
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
KB 3938'; GR 3926'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
REPAIR OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set RBP @ 5700 & spot sand on top, set pkr & press tst casg to 1000 psi. Perf d w/4 holes @ 2641. Set pkr & circ down 2-3/8" tbg & out 4-1/2" x 8-5/8" ann. Pld tbg & RIH w/cmt rtnr & set @ 2590. RIH & stung into rtnr & pmpd 2200 sxs Class "C" neat cmt, yield 1.32, 14.8 ppg. Pump 100 sxs Class "C" cmt w/2% cacl, yield 1.32, 14.8 ppg. Had full rtnrs, did not circ cmt to surf. Ran temp surv which indic T/cmt @ 1874. Perf d 4 holes @ 1674. RIH w/pkr & set @ 1440, pmpd 400 sxs class "C" cmt, yield 1.32, 14.8 ppg & 100 sxs class "C" w/2% cacl, yield 1.32, 14.8 ppg, circ 100 sxs to surf. Displ w/FW. Pld pkr. RIH w/bit & DOC 1551-1684, tstd perfs to 500 psi - ok. DOC 7585-90 & DO cmt rtnr @ 2590. DOC 2592-2650. Tstd csg & perfs to 500 psi - ok. Circ sd off RBP & POOH w/bit. RIH & latch RBP & POOH. RIH & displ w/2% KCL wtr. Set RBP @ 5700 & pkr @ 2140. Loc leak 2647-2616. (Old sqzd perf @ 2640) Pld pkr. Set cmt rtnr @ 2555. Stung into rtnr & pmp 218 sxs cmt. POOH. Drld out cmt, rtnr & cmt fr 2542-2692. Had wtr sli wtr flow. RIH & set cmt rtnr @ 2584. Sqzd w/200 sxs Class "C" cmt below rtnr, Pld out of rtnr & circ. Sting into rtnr @ 2584 & press below rtnr to 1100 psi. Bled dn. Pmp FW dn tbg & press to 2000 psi, opn tbg & press drpd to 1400 psi. Flow back @ 1/2 BPM/30 mins, then 15 GPM. Sting into rtnr & pmp 165 sxs class "C" cmt to 2000 psi. Pmp 200 sxs thickset cmt. POOH w/tbg. RIH & DOC, cmt rtnr & cmt 2580-2657. No flow back. RIH & rev sd off T/RBP. Latch RBP & POOH. RIH w/tbg & LDD @ 6144. Ran P&R & place on production. Work commenced on 8-19-81; work completed on 9-9-81. Prod. prior: Pump 35 Bo, 16 BW & 14 Mcfgpd; Prod. after: Pump 37 BO, 0 BW & 15 Mcfgpd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	B. R. Graham	TITLE	Engineering Technologist	DATE	May 26, 1982
ORIGINAL SIGNED BY					
JERRY SEYTON					
APPROVED BY	TITLE				DATE
JUN 1 1982					
CONDITIONS OF APPROVAL (IF ANY):					

RECEIVED

MAY 28 1982

O.C.D.
HOBBY OFFICE