

Well Name and No. Hondo B ate #1 ate #1 Loc. on: 560' FSL & 1880'
 FEL, Sec. 6, T-19-S, R-35-E, Lea Co., New Mexico Drilled: 1964

Type of Job P&A Field Scharb
 TD 10,207 PBD 10,163 DATUM 15' RKB Elevation KB By: 1964

Wellhead Information: CIW, 12" 900 x 10" 900 x 6" 900

Casing Information:	Size	Wt.	Grade	Set @	Sx Cmt	Top
Surface	<u>13-3/8"</u>	<u>48</u>	<u>H-40</u>	<u>419</u>	<u>400</u>	<u>Circ</u>
Intermediate	<u>8-5/8"</u>	<u>32 & 24</u>	<u>H-40 & J-55</u>	<u>4005</u>	<u>188</u>	<u>Circ</u>
Producing	<u>5-1/2"</u>	<u>15.5 & 17#</u>	<u>N-80 & J-55</u>	<u>10,207</u>	<u>200</u>	<u>9400 TS</u>
Liner						

Present Perf's: From 9561 To 9575 Holes 8 Stimulation Acddz
 From 10,115 To 10,154 Holes 80 Stimulation Acddz

Present Open Hole: Size _____ From _____ To _____ Stimulation _____

Tubing Data: Size 2-7/8" Wt. 6.5 Grade N-80 Thd EUE 8rd Btmd @ 10,155
 Jts 327 Misc. PN, TAC, SN

Packer _____ Depth 10,148 Tension 31,000 Comp _____
 Tbg Anchor X

Miscellaneous: Fiberglass Rods

PROCEDURE

- MIRUPU. POH warehousing rods.
- NU BOP. POH w/prdn tbg.
- RU WL & run GR-JB to 10,100'. Set CIBP @ 9970' & dump 35' cmt. (perfs)
- Set CIBP @ 9500 & dump 35' cmt (perfs).
- RIH w/2-7/8" prdn tbg OE to 9465' & circ w/10# 35 vis MLF & POH.
- Perf 5-1/2" csg @ 7800' w/4 shots.
- RIH w/FBRC & set @ 7700'. Test ann to 500. Est inj & POH.
- RIH w/CR on 2-7/8" prdn tbg & set @ 7700'. Cmt perfs w/100 sx Cl "C" neat. POH w/stinger. (Top of Bone Springs)
- Perf 5-1/2" csg @ 5150' w/4 shots.
- RIH w/FBRC & set @ 5050'. Est inj & POH.
- RIH w/CR & set @ 5050'. Cmt perfs @ 5150' w/100 sx Cl "C" neat. POH. w/stinger (Top of San Andres).
- Perf 5-1/2" csg @ 4060' w/4 shots.
- RIH w/FBRC & set @ 3950'. Est inj & POH.
- RIH w/CR & set @ 3950'. Cmt perfs @ 4060' w/100 sx Cl "C". POH w/stinger
- RU WL & spear 5-1/2" csg. Jet cut 5-1/2" csg @ 3700'. POH LD 5-1/2" csg.
- RIH w/2-7/8" WS OE to 3330'. Spot a 180' cmt plug using 50 sx Cl "C". (Base of salt).
- POH to 2160 & spot a 180' cmt plug using 50 sx Cl "C" (Top of salt).
- POH to 470' & spot a cmt plug to surf using 150 sx Cl "C" neat. POH.
- Cut off wellhead & weld on plate w/valve, install 4" x 4" marker.

RECEIVED
DEC 20 1985
G.C.P.
HOBBS OFFICE