Form 3160-5 June 1990)	DEPARTMENT	ED STATES	M.M. Oil Cons. Div 1625 N. French Dr Hobbs, NM 88240	Budget Bureau No. 1004-0135	
	BUREAU OF L	AND MANAGEMENT	MODDS, NW COZAN	5. Lease Designation and Serial No. NMO52	
	SUNDRY NOTICES	AND REPORTS ON W	ELLS	6. If Indian, Allottee or Tribe Name	
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals				NA	
SUBMIT IN TRIPLICATE				7. If Unit or CA, Agreement Designation Mescalero Ridge Ut. 891007465B	
I. Type of Well Qil Gas Well Well				8. Well Name and No.	
Well U Well Other  Name of Operator				Mescalero Ridge 35UT#	
Devon Energy	y Corporation			9. API Well No.	
3. Address and Telephone 1	No.		100 ((05)005 0011	30-025-21265 10. Field and Pool, or Exploratory Area	
20 N. Broadway, Ste. 1500, Oklahoma City, LK 73102 (405)235-3811 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Pearl (Seven River	
990' FSL & 6 Lea County,	500 FEL, Unit P, S NM	ec.35 TI95 R 25E	4E	Lea County, New Mex	
12. CHECK	APPROPRIATE BOX(	) TO INDICATE NAT	URE OF NOTICE, REPOP	RT, OR OTHER DATA	
TYPE OF	SUBMISSION		TYPE OF ACTION		
Notice	of Intent	Abandon	nent	Change of Plans	
			tion	New Construction	
X Subsequ	uent Report			Won-Routine Fracturing	
		Casing R		Conversion to Injection	
Final Abanc	bandonment Notice			Dispose Water	
				(Note: Report results of multiple completion on V Completion or Recompletion Report and Log for	
give subsurface loc 1) 2-15-00 l 2) 2-23-00 (	ations and measured and the vertic NBLM Steve Caffey Circulate hole w/M	ALF		g any proposed work. If well is directionally di	
$\begin{array}{c} \text{give subsurface loc} \\ 1) & 2-15-00 & 1\\ 2) & 2-23-00 & 3\\ 3) & 2-23-00 & 3\\ 4) & 2-23-00 & 3\\ 5) & 2-24-00 & 3\\ 6) & 2-24-00 & 3\\ 0 & 10 & 5-1/2 \end{array}$	ations and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8".	1LF 280-4044' as per E 3878', WOC & Tag fs @ 1940', spot at. down 5-1/2" cs	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', sg. thru perfs @ 285'	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf	
$\begin{array}{c} \text{give subsurface loc} \\ 1) & 2-15-00 & 1\\ 2) & 2-23-00 & 3\\ 3) & 2-23-00 & 3\\ 4) & 2-23-00 & 3\\ 5) & 2-24-00 & 3\\ 6) & 2-24-00 & 3\\ 10 & 5-1/2 \end{array}$	ations and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8".	11.F 280-4044' as per E 3878', WOC & Tag cfs @ 1940', spot at. down 5-1/2" cs dmen. Install dry	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 5g. thru perfs @ 285 hole marker, backfi	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP	
$\begin{array}{c} \text{give subsurface loc} \\ 1) & 2-15-00 & 1\\ 2) & 2-23-00 & 3\\ 3) & 2-23-00 & 3\\ 4) & 2-23-00 & 3\\ 5) & 2-24-00 & 3\\ 6) & 2-24-00 & 3\\ 10 & 5-1/2 \end{array}$	ations and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8".	Approved Liability un	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', sg. thru perfs @ 285'	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CARLSBAD OF LAND MAR 13 - A & RESOURCEAU OF LAND MESOURCE A	
give subsurface loc 1) 2-15-00 l 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut	ations and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8".	Approved Liability un	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 39. thru perfs @ 285 hole marker, backfi as to plugging of the well born	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CARLSBAD OF LAND MAR 13 - A & CARLSBAD OF LAND MEROPEO RESOURCE A & 2000 MG A & 20	
give subsurface loc 1) 2-15-00 I 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut	ations and measured and true vertice NBLM Steve Caffey Circulate hole w/M Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8". off wellhead dead	ALF 280-4044' as per E 3878', WOC & Tag cfs @ 1940', spot at. down 5-1/2" cs dmen. Install dry Approved Liability un surface re	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 3g. thru perfs @ 285' hole marker, backfi hole marker, backfi as to plugging of the well born ander bond is retained until storation is completed.	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CALLS NO NAR 13 - A & CALLS NO RESOURCE AU OF RESOURCE AU OF RESOURCE AU OF CALLS & COL AU OF CALLS & COL AU AU OF CALLS & COL AU AU AU AU AU AU AU AU AU AU	
give subsurface loc 1) 2-15-00 1 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut 14. I hereby certify that th Signed (This space for Federal	netions and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8". off wellhead dead	Approved Liability un surface re	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 5g. thru perfs @ 285 hole marker, backfi hole marker, backfi storetion is retained unth storetion is completed.	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CAUGE AU OF CAUGE AU OF CAUGE AU OF CAUGE AU OF COMMAND OF COMMAND COMMAND OF COMMAND	
give subsurface loc 1) 2-15-00 I 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut	Altons and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8". off wellhead dead the foregoing is true and correct MMM al or State office use al or State office use	fLF 280-4044' as per E 3878', WOC & Tag cfs @ 1940', spot at. down 5-1/2" cs lmen. Install dry Approved Liability un surface re	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 3g. thru perfs @ 285' hole marker, backfi hole marker, backfi as to plugging of the well born ander bond is retained until storation is completed.	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CAUCER BAD BAR 13 - A & CAUCER BAD OF LAND RESOURCE A & COUNT CAUCER A & COUNT CA	
give subsurface loc 1) 2-15-00 1 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut 14. 1 hereby certify that th Signed (This space for Federa Approved by	Altons and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8". off wellhead dead re foregoing is true and correct MMM al or State office use) Al or State office use) Al if any:	Approved Liability un surface re Tide	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 5g. thru perfs @ 285 hole marker, backfi. as to plugging of the well born or bond is retained unth storation is completed.	CARLSBAD RESOURCE AREA Date 3-02-00 MAR 2 2 2000	
give subsurface loc 1) 2-15-00 I 2) 2-23-00 ( 3) 2-23-00 ( 4) 2-23-00 ( 5) 2-24-00 ( up 5-1/2 7) Will Cut 14. 1 hereby certify that th Signed (This space for Federa Approved by Conditions of approva	Altons and measured and true vertice NBLM Steve Caffey Circulate hole w/N Spot 25 sx cmt. 42 Spot 30 sx cmt. @ Pressure up on per Circulate 80 sx cr " X 8-5/8". off wellhead dead re foregoing is true and correct MMM al or State office use) Al or State office use) Al if any:	Approved Liability un surface re Tide	SLM Steve Caffey TOC @ 3523'. 25 sx cmt. @ 1990', 5g. thru perfs @ 285 hole marker, backfi. as to plugging of the well born or bond is retained unth storation is completed.	COC & tag TOC @ 1819'. ' w/ cmt. circ. to Surf 11 cellar & pit.ASAP CAUGE AU OF RECEIVE AD RESOURCE AD	