

26-60 TD 5327'
 Cored 1' ...
 8-2-65 TD 5327' W/2
 8-9-65 TD 5327', PBD 4683', RC Pump.
 Perf 4604-06', 4894-96' W/2 SPP
 Ac. 500 gals. 4894-96'
 Swbd 19 BLO + 6 BAW/19 hrs & swbd dry.
 Set BP @ 4683'
 Ac. 500 gals. 4604-06'
 Swbd 18 BLO + 6 BAW/8 hrs.
 Pulled BP @ 4683'
 Trac 20,000 gals lse oil + 30,000# sd.
 (-604-4896')
 8-17-65 TD 5327', PBD 4988', pmpg load.
 (No gauge)

8-23-65 TD 5327', PBD 4988', pmpg load.
 Pmpd 16 BLO + 60 BFW/24 hrs.
 8-30-65 TD 5327', PBD 4988', pmpg load.
 Pmpd 11 1/2 BLO + 88 BFW/24 hrs. (-485 BLO)
 9-7-65 TD 5327', PBD 4988', pmpg load.
 Pmpd 14 BLO + 88 BFW/24 hrs. (-388 BLO)
 9-10-65 TD 5327', PBD 4988', pmpg load. (-292 BLO)
 9-20-65 TD 5327', PBD 4988', pmpg load. (-185 BLO)
 9-27-65 TD 5327', PBD 4988', pmpg load. (-89 BLO)
 10-4-65 TD 5327', PBD 4988', 1stg on pump.
 Pmpd 14 BLO + no gauge on wir/24 hrs.
 10-11-65 TD 5327', PBD 4988', prep to potential.
 Pmpd 30 BLO + 182 BFW/24 hrs.
 10-18-65 TD 5327', PBD 4988', COMPLETED.
 100 TOFS. Aubreyrite 1802', Yates 3560',
 Sever Rivers 700', Queen 4590', Grayburg
 5040'.

COUNTY LEA FIELD Pearl Queen STATE NM 2128, OWWO
 OPR MINERALS, INC MAP
 1 Minerals State
 Sec 36, T-19-S, R-34-E CO-ORD
 990' FSL, 1650' FWL of Sec.

Re-Cmp 11-19-68	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
8 5/8" at 200' w/125 sx				
4 1/2" at 5300' w/200 sx				
LOGS EL GR RA IND HC A				
	TD 5327'; PBD 4988'			

(Queen) Peri 4604-4964' NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4964' TYPE WO
 DATE

F.R.C. 12-12-68
 PD 4964' WO
 (Orig Mallard Pet., Inc. #1 State, 10-11-65 thru peris 4604-4896', OIB 4988', OPB 4988')
 12-9-68 TD 5327'; PBD 4988'; COMPLETE
 Peri 4731-33', 4764-69', 4900-04', 4954-64'
 w/L SPF
 Acid (4731-4964') 1000 gals
 Frac (4731-4964') 20,000 gals brine + 20,000# sd
 Ppd 12 BO + 40 BW in 24 hrs (4604-4964')
 12-12-68 COMPLETION REPORTED