

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

APR 15 2 35 PM '66

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

April 15, 1966
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

HONDO DRILLING COMPANY Midway State "A" Well No. 1 in I
(Company or Operator) Lease (Unit)
NE ¼ SE ¼ of Sec. 8, T. 17 South, R. 37 East, NMPM, Midway Abo Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

A string of 4½", 11.60# casing composed of 1100' of N-80 and 7580' of J-55 has been run and cemented at depth of 8660' with 165 sacks of Inco Posmix with 2% Jel and 8# salt per sack. Plug was pumped down at 10:30 A.M. April 14, 1966.

After cement has been allowed a set time of 24 hours, the casing will be perforated in the Abo section as follows: 2-jet shots each interval 8495, 8500, 8503, 8506, 8511, 8514, 8518, 8553, 8559, 8564, 8568, 8591, 8597, 6607, 8612, 8618.

After perforating has been completed, tubing will be run with packer to be set above perforations. Perforated interval will then be washed with 1000 gallons of Mud acid. Top of plug in 4½" casing is at 8645'.

Additional acid will be used as seems advisable.

Approved....., 19.....
Except as follows:

Hondo Drilling Company
Company or Operator
By.....

Position..... Agent
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name..... Charles P. Miller

Title.....

Address..... P. O. Box 417, Hobbs, N.M.