

COUNTY	LEA	FIELD	Midway-Abo	STATE	NM
OPR	RHCDES & RICHARDSON				MAP
	1 Midway-State				
	Sec. 8, T-17-S, R-37-E				CO.ORD
	1650' fr S Line & 710' fr E Line of Sec.				
	Spd 9-27-65;				EA [REDACTED]
	Cmp 10-24-65;				CLASS
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
11 3/4" at 337' w/300 sx					
8 5/8" at 4399' w/375 sx					
LOGS EL GR RA IND HC A					
	TD 8952';				
PLUGGED & ABANDONED.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Forster Drlg. Co.	PROP DEPTH	9000'	TYPE
DATE				

F.R. 9-16-65; Opr's Elev. 3786' DF
PD 9000' - Abo
Contractor - Forster Drlg. Co.
10-4-65 Drlg. 4138'
10-11-65 Drlg. 5960'
10-18-65 Drlg. 8085'
10-25-65 TD 8952'; PLUGGED & ABANDONED
SP DST 8530-8663', no recovery, FP 332#;
Re-Set pkrs @ 8750' & 8883', open 1 hr, rec 659'
mud, 1 hr ISIP 511#, FP 345-319#, 1 hr FSIP 345#;
LOG TOPS: Rustler 2020', Base Salt 3095', Yates
3215', Seven Rivers 3788', Queen 4160', San Andres
4910', Glorieta 6464', Tubb 7810', No Abo Reef
present;

COUNTY		LEA		FIELD		Midway		STATE		NM		OWWC	
OPR		HONDO DRILLING CO.										MAP	
		1 Midway-State "A"											
		Sec. 8, T-17-S, R-37-E										CO-ORD	
		1650' FSL, 710' FEL of Sec.											
		Re-Cmp 5-6-66		CLASS		OWWC		EL					
				FORMATION		DATUM		FORMATION		DATUM			
		SG & SX - TUBING											
		11 3/4" 329' 300											
		8 5/8" 4399' 375											
		4 1/2" 8680' 165											
LOGS		EL GR RA IND HC A											
						TD 8952'							

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.
DATE

PROP DEPTH 8500-8700' TYPE WO

F.R. 4-14-66; OWWC
(Orig. Rhodes & Richardson #1 Midway-State,
PSA 10-24-65, OFD 8952')
Elev. 3785' DF, Orig.
PD 8500-8700' - Abo
4-19-66 TD 8952', PED 8680', prep to swab.
CO & Ran 4 1/2" casing
Perf (Abo) @ 8495', 8500', 8503', 8506',
8511', 8514', 8518', 8553', 8559', 8564',
8568', 8591', 8597', 8607', 8612', 8618'
W/2 SPI
Ac (8495-8618') 1000 gals (15%); Break-
down pressure 3900#
Swbd dry, NS (8495-8618')
Ac (8495-8618') 3000 gals.
Swbd dry (8495-8618')
Ac (8495-8618') 5000 gals.

26-66 TD 8952', PBD 8680', swbg.
Swbd mud & emulsion, NS (8495-8618')
5-3-66 TD 8952', PBD 8680', prep to P&A.
Ac (8495-8618') 20,000 gals.
Swbd acid wtr, w/sli show oil & gas
(8495-8618')
Did not rec load (8495-8618')
5-9-66 TD 8952', PBD 8680', COMPLETE.