

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 5000 feet, and from _____ feet to _____ feet.
Cable tools were used from none feet to _____ feet, and from _____ feet to _____ feet.

Put to Producing.....**January 11**....., 19**65**

OIL WELL: The production during the first 24 hours was 5 1/2 barrels of liquid of which 2.67 % was
was oil; 0 % was emulsion; .38 % water; and 0 % was sediment. A.P.I.
Gravity 38 at 60°

GAS WELL: The production during the first 24 hours was.....None.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....none.....lbs.

Length of Time Shut in 24 hrs.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Northwestern New Mexico

SOUTHWESTERN NEW MEXICO		NORTHWESTERN NEW MEXICO	
T. Anhy.....	1622	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	1750	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	2760	T. Montoya.....	T. Farmington.....
T. Yates.....	2955	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	--	T. McKee.....	T. Menefee.....
T. Queen.....	3930	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	4635	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	4660	T. Granite.....	T. Dakota.....
T. Glorieta.....		T.	T. Morrison.....
T. Drinkard.....		T.	T. Penn.....
T. Tubbs.....		T.	T.
T. Abo.....		T.	T.
T. Penn.....		T.	T.
T. Miss.....		T.	T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	30	30	Surface Sand	4742	5001	259	Lime
30	61	31	Caliche	5001	5600	599	Dolomite T.D.
61	126	65	Gravel				
126	480	354	Redbed				
480	1538	1058	Shale				
1538	1622	84	Shaly & Anhydrite				
1622	1750	128	Anhydrite				
1750	2760	1010	Salt				
2760	2955	195	Anhydrite				
2955	3062	107	Lime & Sand				
3062	3410	348	Anhydrite				
3410	3738	328	Anhydrite & Lime				
3738	3930	192	Lime				
3930	3980	50	Sand & Lime				
3980	4405	425	Dolomite				
4405	4660	255	Lime				
4660	4715	55	Dolomite & Lime				
4715	4742	27	Porous Lime				

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 19, 1965

Company or Operator ROY H. SMITH DRILLING CO.
Name ROY H. SMITH

(Date) _____
Address 728 1st. Wichita National Bldg.
Wichita Falls, Texas
Position or Title Sole Owner