

COUNTY	LEA	FIELD	Vacuum	STATE	NM
OPR	STANDARD OIL COMPANY OF TEXAS				MAP
10 State "6-34"					
Sec. 34, T-17-S, R-35-E				CO-ORD	
940' fr S Line & 1650' fr W Line of Sec.					
Spud 3-10-65		CLASS		E [REDACTED]	
Comp 4-17-65		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Tansill 2884			
		Yates 3005			
8 5/8" 1636'		7-R 3190			
4 1/2" 4650' 800		Queen 3902			
		Grayb 4163			
		SA 4544			
LOGS EL GR RA IND HC A					
		TD 4650', PBD 4611'			

IP San Andres Perfs 4545-75' Pmpd 51 BOPD + 4 BW. Pot. Based on 24 hr test, gravity 37.1, GOR 1225.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Johnn Drlg. Co.	PROP DEPTH 4700'	TYPE
DATE		

F.R. 2-25-65
PD 4700' - SA
Contractor - Johnn Drlg. Co.

3-15-65 Drlg. 3600'.
3-22-65 TD 4650', prep to log.
Cored 4490-4543', rec 53' dolo., w/scatt shows.
Cored 4543-96', rec 53' dolo., w/scatt shows.
Cored 4596-4650', rec 54' dolo., w/scatt shows.

3-29-65 TD 4650', prep to perf.
4-5-65 TD 4650', swbg.
Perf @ 4545', 4547', 4549', 4551', 4555',
4557', 4569', 4571', 4573', 4575' W/1 SPI.
Ac. 500 gals.
Swbd 7 BLO + 9 BNO & 21 BFW in 11 hrs.

4-12-65 TD 4650', PBD 4611', WO Pump.
4-19-65 TD 4650', PBD 4611', COMPLETED.

307125 01202

COUNTY LEA FIELD Vacuum STATE NM OWWO
OPR STANDARD OIL CO. OF TEXAS MAP
10 State 6-34
Sec. 34, T13S, R35E CO-ORD
940' PSL, 1650' FWL of Sec.

		CLASS		OWDF EL	
Re-Cmp	7-8-68	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8"	1636'	800			
4 1/2"	4650'	800			
LOGS EL GR RA IND HC A					
		TD 4650', PBD 4611'			

San Andres Perfs 4545-99' - NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 4599' TYPE WO

8-5-68 F.R.C. 8-8-68; OWWO
PD 4599' - SA
(Orig. Cmp 4-16-65 thru SA Perfs 4545-75', OTD
4650', OPB 4611')
Elev. 3929' GL
TD 4650', PBD 4611', COMPLETE
Perf @ 4577', 4579', 4584', 4594', 4596',
4599' W/1 SPI
Acid (4577-99') 5000gals (15%)