

U. S. DEPT.
OF THE INTERIOR

CAYAL DR 21-3
(LINAM FORM NO. 1)
SECTION 21-185-52E
660' FRL 1930' FSL
LEA COUNTY, NEW MEXICO

SURFACE CSG: 13 5/8", 48# @ 753'
13 5/8", 48# @ 753' INT. CIRC
INTERM. CSG: 8 5/8", 24#-32# @ 3465'
PRODUCTION CSG: 5 1/2", 17# @ 10,787'
GL: 3760 KB: 5774 TD: 11,747

8 5/8", 24-32# @ 3465'
INT. CIRC

5 1/2" 17# ID: 4.892" DRIFT 4.767

COLLAPSE 4910# BURST 5320

STAND
1,600 - 1,700
Top Line -
8500'
6" 85T
Production

~ ENT TOP 8300'
CIBP
10,052'
(BONES SPRINGS)
8708-8716
502 w/100 SX
(WOLF CAMP)
10502-516
10605-712 } 502 w/300 SX
5 1/2", 17# @ 10,787'

SPOT 50 SX @ 10,287'

7 7/8" Hole To 11,747'

SPOT 25 SX @ 11,727'

SPOT 25 SX @ 12,244'

TD 12813'

Completion Record

WOLF CAMP
11-15-85: P/10,655-712 A/5200

WOLF CAMP
12/14,502-516 A/2800

BONES SPRINGS
12/8708-8716 A/5000

QUALITY COMPLETED WELL

1-27-67: 502 BONES SPRINGS 8708-8716
w/100 SX

2-24-82: 502 WOLF CAMP P/10,502-712
w/100 SX.

DILLO 10,787-12813 (MURROW TEST)
UNSUCCESSFUL, PLUGGED WELL TO SURF.

10-19-85: REENTRANCE TO 9700'

2-22-89: RAN CSG INSP LOG 9900-9000
CBL 9900-9000

TCB 10/25/90

RECEIVED

JUL 13 1995

JOHN HOBBS
OFFICE