

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

TE
re

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 0555296

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Llano Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Querecho Plains

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T. 18S., R. 32E.

12. COUNTY OR PARISH

Lee

13. STATE
New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

International Oil & Gas Corporation

3. ADDRESS OF OPERATOR

P. O. Box 427, Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FEL Section 21, T. 18S., R. 32E.,
Lee County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3764 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 23 jts. (739.7') 13 3/8", 48#, H-40 STC casing, set and cemented at 753' with 425 sks. Incor-Pozmix plus 6% gel and 2% cacl followed by 150 x. Incor plus 2% CaCl. Circulated 60 sks to pit. Plug down at 11:30 P.M. 9-17-65. WOC

C.O.C. 22 hr. 45 min. Tested casing at 1000 psi for 30 minutes, pressure held okay. Drilled out at 10:15 P.M. 9-18-65. Now drilling ahead with 11" bit and clear water.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harold E. Brown

TITLE

District Engineer

DATE

9-21-65

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Item 4: If there are no applicable Federal, State or Federal office for specific instructions, submit to applicable Federal, State or Federal office for specific instructions. Any necessary special conditions for submitting proposals in addition, such proposals to above plugs, amount conditioned for.

Instructions

1. is to perform certain well operations, and reports of such operations when completed, as indicated, on Federal regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

ate requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local instructions.

"don a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant " off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and " size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site "w, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site nal inspection looking to approval of the abandonment.