

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

N. M. 052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Ernest A. Hanson

3. ADDRESS OF OPERATOR

P. O. Box 1515, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' FNL & 990' FWL

Sec. 35, T. 19 S., R. 34 E., NMPM

Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3732' KB

7. UNIT AGREEMENT NAME

Mescalero Ridge

8. FARM OR LEASE NAME

Mescalero Ridge U 35

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Pearl Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35 - 19S - 34E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The captioned well was re-entered with rotary tools on 7-13-66 to a depth of 5050'. 5-1/2", 15-1/2 lb., J-55 casing was set at 5050' and cemented with 350 sx. neat Incor. 1000 lbs. press. was held on casing for 24 hours with no leak-off.

7-20-66 Perf. 1 - 0.35" SPF @ 4599, 4601, 4612, 4614, 4625, 4629, 4768, 4769, 4862, 4863, 4864 & 4865'.

7-21-66 Frac. w/1000 gals. acid + 30,000 gals. lease oil + 20,000 lbs. sand.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry F. Schenck

TITLE

Explor. Mgr.

DATE

8-6-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side