

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRICATE*
(Other instruct
verse side)Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A DIFFERENT RESERVOIR.")

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry hole		5. LEASE DESIGNATION AND SERIAL NO. N.M. 052	
2. NAME OF OPERATOR Ernest A. Hanson		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico		7. UNIT AGREEMENT NAME Mescalero Ridge	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' ENL & 990' FWL Sec. 35, T. 19 S., R. 34 E., NMPN Lea County, New Mexico		8. FARM OR LEASE NAME "35" Mescalero Ridge Unit	
14. PERMIT NO.		9. WELL NO. 14	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3732' KB		10. FIELD AND POOL, OR WILDCAT Pearl Queen	
		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35 - 19S - 34E	
		12. COUNTY OR PARISH Lea	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Verbal approval was given by Mr. A. R. Brown this date to plug and abandon the captioned well in the following manner:

Total depth 5197' dolomite.
Top of Queen Fm. @ 4567'.
Base of Salt @ 3341'.
Top of Salt @ 1925'.
8-5/8" casing set @ 206'.

Cement plugs are to be set in heavy mud as follows:

30 sack cement plug @ 4507-4607'.
30 sack cement plug @ 3291-3391'.
30 sack cement plug @ 1875-1975'.
30 sack cement plug @ 156-256'.
10 sack cement plug @ surface & regulation marker erected.

The location will then be cleaned up and made ready for USGS inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry F. Schram

TITLE

Geologist

DATE Dec. 21, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DEC 27 1965

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER