

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPLICATE*
(Other instruct on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

MOBES OFFICE O.C.C.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back into a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

| | | |
|--|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. N. M. 052 |
| 2. NAME OF OPERATOR Ernest A. Hanson | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico | | 7. UNIT AGREEMENT NAME Mescalero Ridge |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & FEL Sec. 35, T. 19 S., R. 34 E., NMPM Lea County, New Mexico | | 8. FARM OR LEASE NAME "35" Mescalero Ridge Unit |
| 14. PERMIT NO. | | 9. WELL NO. 15 |
| 15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3732' KB | | 10. FIELD AND POOL, OR WILDCAT Pearl Queen |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35 - 19S - 34E |
| | | 12. COUNTY OR PARISH Lea |
| | | 13. STATE N. Mex. |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-4-66 Spud well this date. Ran 7 joints of new, 8-5/8", 24#, H-40 casing to 229' and cemented with 150 sacks regular with 2% CaCl. Cement circulated to the surface.

3-5-66 WOC 24 hours. Pressure tested casing to 600 lbs. for 30 minutes. No. leaks. Prep. to drill ahead.

APPROVED

MAR 11 1966

J. L. GORDON

ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry J. Schuman

TITLE

Geologist

DATE

3-8-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side