

COUNTY LEA FIELD Pearl-Queen STATE NM
 OPR ST. CLAIR, D. W. MAP
6 Superior-Federal
Sec. 25, T-19-S, R-34-E CO-ORD
990' FSL, 1650' FWL of Sec. MN 21745
Spd 3-23-66 CLASS
Cmp 4-19-66 EL

CSG & SX - TUBING	FORMATION		DATUM	
	FORMATION	DATUM	FORMATION	DATUM
8 5/8" 248' 125				
5 1/2" 5139'				
LOGS EL GR RA IND HC A				
	TD 5150', PBD 5139'			

IP Queen Perfs 4811-5015' Pmpd 64 BOPD + 10 BW. Pot. Based on
 24 hr test, gravity 35., GOR 625.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Leatherwood Drlg. Co. PROP DEPTH 5200' TYPE
 DATE

F.R. 3-31-66; Opr's Elev. 3730' GL
 PD 5200' - Queen
 Contractor - Leatherwood Drlg. Co.
 4-4-66 TD 5150', running logs.
 4-11-66 TD 5150', PBD 5139', rec'g load.
 Perf @ 4811', 4814', 4899½', 4903',
 4967', 4971½', 4992', 5011', 5015' W/1 SPI
 Frac (4811-5015') 30,000 gals +
 30,000# sd.
 4-18-66 TD 5150', PBD 5139', rec'g load.
 4-25-66 TD 5150', PBD 5139', WO Potential.
 Pmpd 64 BØ + 10 BW/24 hrs, gravity 35.,
 GOR 625.
 5-2-66 TD 5150', PBD 5139', COMPLETED.
 LOG TOPS: Anhydrite 1807', Salt 1932',
 Yates 3535', Queen 4615', Penrose 4938'.