

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 4 1 03 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
State - K - 4772

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	NONE
3. Address of Operator	8. Farm or Lease Name
TEXACO Inc.	State N. M. "DE"
4. Location of Well	9. Well No.
UNIT LETTER E, 1980 FEET FROM THE North LINE AND 622 FEET FROM	2
THE West LINE, SECTION 18 TOWNSHIP 17-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat
	Midway Abo
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
Not Available	Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 353'
Spudded 15" Hole at 9:00 P. M. April 29, 1966

Ran 336' of 11 3/4" O. D. Casing, 23.72 LB., Spiral Weld, NEW, and cemented at 353' with 300 Sx. Incor Neat. Plug at 326'. Cement Circulated.

Temperature of mixing slurry - 75°, Temperature of Water - 68°.
14 Hour Strength - 1000 P. S. I., Job complete 10:00 A. M. April 30, 1966.

Tested 11 3/4" O. D. Casing for 30 minutes with 600 P. S. I. from 2:30 A. M. to 3:00 A. M. May 1, 1966. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 3:30 A. M. to 4:00 A. M. May 1, 1966. Tested O. K. Job complete 4:00 A. M. May 1, 1966.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan Gillett TITLE Assistant District Superintendent DATE May 2, 1966

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: