Forn 1160-5 (August 1999)

IT-IVI. UII UUIIS, DIVISIOII

1625 N. Frer h.Dr. Hobbs, NM 88240


FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

UNI.LD STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Lease Serial No.	
NM-052	

SUNDRY NOTICES AND REPORTS ON WELLS	NM-052		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE • Other instructions on reverse side 1. Type of Well	7. If Unit or CA/Agreement, Name and/or No.		
☐ Oil Well ☐ Gas Well ☒ Other Water Injection Well	8. Well Name and No.		
2. Name of Operator Devon Energy Production Co., L P	Mescalero Ridge Unit "25" #16		
3a. Address 20 N.Broadway, Suite 1500, Okla City, OK 73102 3b. Phone No. (include area code) (405)552-4528	30-025-21858 10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990' FSL & 1650' FEL of Section 35-T19S-R34E Unit O	Pearl (Queen) Field 11. County or Parish, State Lea County, New Mexico		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACTION			
Notice of Intent Acidize Deepen Production (Start Alter Casing Fracture Treat Reclamation New Construction Recomplete Change Plans Plug and Abandon Temporarily Aba Convert to Injection Plug Back Water Disposal Convert to Injection periode the Bond No. on file with BLM/BIA. Required following completion of the involved operations. If the operation results in a multiple completion or recompletion in testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamated determined that the site is ready for final inspection.	Well Integrity Other or proposed work and approximate duration thereof rical depths of all pertinent markers and zones. Subsequent reports shall be filed within 30 days a new interval or Form 2160 A shall be filed.		
REVISED PROCEDURES Devon Proposes To Permanitly Plug And Abandon As Follows:			
 Set CIBP at 4,550' and cap CIBP with 35' of cement. Cut off 5 1/2" casing at 3,430'. Circulate wellbore full of 9.5 ppg mud. Spot balanced cement plug 3,330'- 3,480' (base of salt at 3,380'). WOC. Tag plug. Spot balanced cement plug 1,770'- 1,870' (top of salt at 1,867'). WOC. Tag plug. Spot cement plug 170'- 270' (surface casing shoe at 217'). WOC. Tag plug. Spot cement plug 0'- 50'. Cut off 8 5/8" casing 3' below ground level and install dry hole marker. Restore location. 			
Note: Cement to be Class "C" at 14.8ppg with a yield of 1.32 cu ft/sx.			
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Charles H. Carleton Title Senior Engineering Tech	nician		
Signature Date 01/28/2002			
APPROVE DHIS SPACE FOR FEDERAL OR STATE OFFICE USE			
Approved by DRIG. S. DR. GLAS Title	Date		
	TACHED FOR S OF APPROVAL		


Title 18 U.S.C. Section TOO DEALENIE EE Pay person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



, \$\frac{1}{2} \cdot \frac{\delta}{2}

DEVON ENERGY CORPORATION WELLBORE SCHEMATIC

WELL NAME: MESCALERO RIDGE UNIT "35" #16			FIELD: PEARL (QUEEN)				
LOCATION: 990' FSL & 1650' FEL, SEC 35-T19S-R34E			COUNTY: LEA			STATE: NM	
ELEVATION: GL=3703'; KB=3715'			SPUD DATE: 10/05/66		COMP DATE: 11/05/66		
API#: 30-025-21858 PREPARED BY		Y: C.H. CARLETON			DATE: 01/28/02		
	DEPTH		SIZE	WEIGHT	GRADE	THREAD	HOLE SIZE
CASING:	0' - 217'		8 5/8"	24#	H-40	ST&C	12 1/4"
CASING:	3430' - 5150'		5 1/2"	15.5#	J-55	LT&C	7 7/8"
CASING:							
TUBING:							
TUBING:							



CURRENT

PROPOSED

OPERATOR: DEVON ENERGY PRODUCTION COMPANY, L.P.

CEMENT PLUG: 0'- 50' **CEMENT PLUG: 170'- 270'**

8 5/8" CASING @ 217' W/250 SXS. TOC @ SURFACE.


NOTE: 9.5PPG MUD TO BE SPOTTED BETWEEN CEMENT PLUGS.

CEMENT PLUG: 1770'- 1870' TOP OF SALT @ 1867')



CEMENT PLUG: 3330'- 3480' (BASE OF SALT @ 3380')

CUT OFF 5 1/2" CASING @ 3430'



CIBP @ 4550', CAPPED WITH 35' CEMENT

PERFORATIONS: 4582'- 4986' (OA) - 22 HOLES

CIBP @ 5098'

5 1/2" CASING @ 5150' W/350 SXS. TOC @ 3910' (TEMP SURVEY)

TD @ 5150'

