

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.C.
NEW MEXICO OIL CONSERVATION COMMISSION

Nov 17 1 37 PM '66

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
State - B-4704	

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name West Lovington Unit
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name West Lovington Unit
3. Address of Operator P. O. Box 728 - Hobbs, New Mexico	9. Well No. 57
4. Location of Well UNIT LETTER <u>H</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>989</u> FEET FROM THE <u>East</u> LINE, SECTION <u>8</u> TOWNSHIP <u>17-S</u> RANGE <u>36-E</u> NMPM.	10. Field and Pool, or Wildcat West Lovington
15. Elevation (Show whether DF, RT, GR, etc.) Not Available	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
-------------------------	-----------------------

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 360'
 Spudded 11" Hole at 12:00 Midnight November 14, 1966

Ran 348' of 7 5/8" O. D. Casing, 15.28 LB, Spiral Weld, NEW, and cemented at 360' with 200 Sx. Class "C" cement with flocele, and 50 Sx. Class "C" cement with 2% CC. Plug at 335'. Cement Circulated.

Temperature of mixing slurry - 57° - 12 Hour Strength, 1000 P. S. I.
 Job complete 10:30 A. M. November 15, 1966.

Tested 7 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 10:30 P. M. to 11:00 P. M. November 15, 1966. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 12:30 A. M. to 1:00 A. M. November 16, 1966. Tested O. K. Job complete 1:00 A. M. November 16, 1966.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan Gillett TITLE Assistant District Superintendent DATE November 16, 1966

APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY: