

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Avenue, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-025-21907

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-2245

7. Lease Name or Unit Agreement Name:

Central Vacuum Unit

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Chevron USA, Inc.

8. Well No.  
19

3. Address of Operator  
15 Smith Rd. Midland, Tx 79705

9. Pool name or Wildcat  
Vacuum, Grayburg, S.A.

4. Well Location

Unit Letter K : 1650 feet from the south line and 1750 feet from the west line

Section 30 Township 17-S Range 35-S NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Tag 5 1/2 CIBP @ 4447 mix & pump 25sx plug fr/4447-4247(Grayburg-San Andres)Tag @ 4125
2. Displace hole w/MLF 9.5# Brine w/25# Gel p/BBL.
3. Spot 25sx plug fr/2700-2500(Yates, B-salt)Tag @ 2469
4. Spot 25sx plug fr/1600-1400(T-salt)Tag @ 1332
5. Spot 65sx plug fr/600-surf(8 5/8 shoe, surf)Tag @ surf
6. Install dry hole marker 2-4-03

Approved as to Plugging of the Well Bore.  
Liability under bond is retained until  
Surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jimmy Bagley TITLE MANAGER / SUNSET DATE 2-4-03

Type or print name Jimmy BAGLEY Telephone No. 915 520-8756  
(This space for State use)

APPROVED BY Gayle W. Wink OC FIELD REPRESENTATIVE II/STAFF MANAGER  
Conditions of approval, if any: TITLE DATE

FEB 14 2003