UNI7__ STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M. Oll Cons. Division Expres

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELDS 18. French DIM-04452

Date

SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Soil Well Gas Well	8. Well Name and No.							
2. Name of Operator Devon Energy Production	Mescale	Mescalero Ridge Unit "26" #5						
3a. Address	9. API Well No. 30-025-22081							
3a. Address 20 N.Broadway, Suite 1500, Okla City, OK 73102 3b. Phone No. (include area code) (405)552-4528 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1650' FSL & 1980' FWL of Section 26-T19S-R34E Unit K					and Pool, or Exploratory Area			
					Pearl (Queen) Field 11. County or Parish, State Lea County,			
								12 CHECK AI
	PPROPRIATE BOX(ES) T	-		REPORT, C	OR OTHER DATA			
TYPE OF SUBMISSION		TY	PE OF ACTION					
Notice of Intent	Acidize Alter Casing	Deepen	Production (St	art/ Resume)	☐ Water Shut-Off			
☐ Subsequent Report	Casing Repair	Fracture Treat New Construction	☐ Reclamation ☐ Recomplete		☐ Well Integrity			
Final Abandonment Notice	Change Plans	☐ Plug and Abandon	Temporarily A	bandon	☐ Other			
	Convert to Injection	Plug Back	☐ Water Disposa					
tonowing completion of the my	nal Abandonment Notices shall be y for final inspection.)	a results in a multiple comp	letion or recompletion	in a new inter-	or an perintent markers and zones, reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has			
Devon Proposes To Perm	nanitly Plug And Abandor	As Follows:						
1. Set CIBP at 4,600' and 2. Cut off 5 1/2" casing at 3. Circulate wellbore full of 4. Spot balanced cement 5. Spot balanced cement 6. Spot cement plug 185'-7. Spot cement plug 0'- 50 8. Cut off 8 5/8" casing 3' 9. Restore location	t 3,390'. of 9.5 ppg mud. plug 3,290'- 3,440' (base plug 1,830'- 1,930' (top o - 285' (surface casing sh 0'.	e of salt at 3,300'). W of salt at 1,932'). WC oe at 235'). WOC. T	DC. Tag plug. ag plug.					
Note: Cement to be Class	"C" at 14.8ppg with a yie	eld of 1.32 cu ft/sx.						
14. I hereby certify that the foregoin	ng is true and correct	1						
Name (Printed/Typea) Charles H. Carleton		Title Senior	Engineering Ted	chnician				
Signature		Date						
Markey II PAIR		01/25/2	2000					

which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. See Earl 3012 makes it accrime for any person knowingly and willfully to make to any department fraudulent statements or representations as to any matter within its jurisdiction.

Office

Conditions of approval, if any, are attached. Approval of this notice does not warrant or

certify that the applicant helds legal or equitable title to those rights in the subject lease

Approved by


TNOW COST LABRUA ED PRO LUGARIOR

82:6 MA 85 HAL 5005

BECEINED

DEVON ENERGY CORPORATION WELLBORE SCHEMATIC

WELL NAME: MESCALERO RIDGE UNIT "26" #5				FIELD: PEARL (QUEEN)				
LOCATION: 1650' FSL & 1980' FWL, SEC 26-T19S-R34E				COUNTY: LEA	STATE: NM			
ELEVATION: GL=3739'; KB=3751'				SPUD DATE: (04/04/67	COMP DATE:	OMP DATE: 05/01/67	
API#: 30-025-22081 PRE		PREPARED E	PREPARED BY: C.H. CARLETON		DATE: 01/25/02			
	DEPTH		SIZE	WEIGHT	GRADE	THREAD	HOLE SIZE	
CASING:	0' - 235'		8 5/8"	24#	H-40	ST&C	12 1/4"	
CASING:	3390' - 5159'		5 1/2"	15.5#	J-55	LT&C	7 7/8"	
CASING:								
TUBING:								
TUBING:								



CURRENT

PROPOSED

OPERATOR: DEVON ENERGY PRODUCTION COMPANY, L.P.


CEMENT PLUG: 0'- 50' CEMENT PLUG: 185'- 285'

8 5/8" CASING @ 235' W/200 SXS. TOC @ SURFACE.

NOTE: 9.5PPG MUD TO BE SPOTTED BETWEEN CEMENT PLUGS.



CEMENT PLUG: 1830'- 1930' (TOP OF SALT @ 1932')



CEMENT PLUG: 3290'- 3440' (BASE OF SALT @ 3340')

CUT OFF 5 1/2" CASING @ 3390'

CIBP @ 4600', CAPPED WITH 35' CEMENT

PERFORATIONS: 4638'- 5006' (OA) - 92 HOLES

PBTD @ 5154'

5 1/2" CASING @ 5159' W/350 SXS. TOC @ 3620' (TEMP SURVEY)

TD @ 5174'

3002 JAN 28 MA 9: 58

BECEINED