

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other Instruc
verse side)LOCATE
4 on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 05519

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Ernest A. Hanson

3. ADDRESS OF OPERATOR

P. O. Box 1515, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface1650' FSL & 1980' FEL
Sec. 26, T-19-S, R-34-E, NMPM
Lea County, New Mexico

7. UNIT AGREEMENT NAME

Mescalero Ridge

8. FARM OR LEASE NAME

"26"

Mescalero Ridge Unit

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26 - 19S - 34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3742' GL

12. COUNTY OR PARISH

13. STATE

Lea

N. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-15-67 The captioned well was plugged and abandoned in the following manner:

Total Depth @ 5160' dolomite
Top of Queen Fm. @ 4629'
Base of Salt @ 3335'
Top of Salt @ 1938'
8-5/8" casing set @ 211'

Cement plugs were sen in heavy mud as follows:

30 sack cement plug @ 4579-4679'
30 sack cement plug @ 3285-3385'
30 sack cement plug @ 1888-1988'
30 sack cement plug @ 161-261'
10 sack cement plug @ surface and regulation marker erected.

The location was then cleaned-up and made ready for USGS inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Henry F. Johnson

TITLE Exploration Manager

DATE 8-21-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED DATE

DEC 4 1967

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER