

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other Instruc
verse side)ICATE*
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 05519

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Mescalero Ridge

8. FARM OR LEASE NAME "26"

Mescalero Ridge Unit

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26 - 19S - 34E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR

Ernest A. Hanson

3. ADDRESS OF OPERATOR

P. O. Box 1515, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1650" FSL & 1980" FEL
Sec. 26, T-19-S, R-34-E, N.M.P.M.
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3742' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Verbal approval was given by Mr. A. R. Brown on 8-13-67 to plug and abandon the captioned well in the following manner:

Total Depth @ 5160' dolomite
Top of Queen Fm. @ 4629'
Base of Salt @ 3335'
Top of Salt @ 1938'
8-5/8" casing @ 211'

Cement plugs are to be set in heavy mud as follows:

30 sack cement plug @ 4579-4679'
30 sack cement plug @ 3285-3385'
30 sack cement plug @ 1888-1988'
30 sack cement plug @ 161-261'
10 sack cement plug @ surface & regulation marker erected.

The location will then be cleaned up and made ready for USGS inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry P. Schramm

TITLE

Exploration Manager

DATE

8-16-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

AUG 18 1967

A. R. BROWN
DISTRICT ENGINEER

DATE

*See Instructions on Reverse Side