

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruct on re-
verse side)Form ap-
Budge- No 42 R1424.
DESI- SERIAL NO.

05

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		6. INDIAN, ALLOTTEE OR TRIBAL NAME
2. NAME OF OPERATOR Ernest A. Hanson		7. UNIT AGREEMENT NAME Mescalero Ridge
3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico		8. FARM OR LEASE NAME "26" Mescalero Ridge Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FSL & FWL Sec. 26, T-19-S, R-34-E, N.M.P.M. Lea County, New Mexico		9. WELL NO. 7
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT Pearl Queen
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3740' KB		11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 26 - 19S - 34E
		12. COUNTY OR PARISH Lea
		13. STATE N. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-4-67 Commence drilling. T.D. 223' red beds. Ran 8-5/8", 24#, H-40 casing @ 223' w/200 sx. reg. + 2% CaCl. Cement circulated to the surface.

11-5-67 W.O.C. 24 hours. Pressure tested casing to 600 lbs. for 30 minutes. No leaks. Prep. to drill ahead.

11-10-67 T.D. 5025' dolo. Running logs.

11-21-67 T.D. 5025' dolo. Ran 5-1/2", 15-1/2#, J-55 casing @ 5025' w/350 sx. neat Incor cement. W.O.C. 24 hours. Pressure tested 24 hours @ 1000 lbs. w/no leaks.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry F. Schuman

TITLE

Exploration Manager

DATE

Nov. 27, 1967

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER