

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPI
(Other instructions
verse side)TE
reForm approved.
Budget Bureau No. 42-R1424.

USGS OFFICE SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen, plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-030941

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BATE Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

26-19-33 NMPM

12. COUNTY OR PARISH

LEA

N.M.

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL x 1980' FWL Sec. 26 (UNIT N. SE/4 SW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3603' R. D. B

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

On 5-7-68, 5 1/2" OD 14# J-55 casing was set @ 3397'.
First stage cemented w/ 85 sz Incon meat + 2% CACH.
Second stage three DV Tool set @ 2922' w/ 1300 sz
Incon + 4% Gel + 1% CACH. Cement circulated (35004)
(USGS REPRESENTATIVE WITNESSED CEMENTING OPERATIONS)
Tested casing w/ 2000 psi for 30 min. Test O.K.

Perforated w/ 1 Shot @ 2a interval, 3350, 57, 61, 64, 74, 76, 78,
85, 88, 90. Acidized w/ 1000 gal MCA. Evaluated.

PT. Swab 13780 x 3BLW in 4 hours. GOR NA. Cgr. 34°

18. I hereby certify that the foregoing is true and correct

SIGNED

William J. Gordon

TITLE

AREA FOREMAN

DATE

5-13-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

MAY 14 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

0-4- USGS-H
1- NSW
1- SUSP
1- RRY