

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY, C.SUBMIT IN TRIPLI
(Other instructions
reverse side)E
re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ DRY HOLE	5. LEASE DESIGNATION AND SERIAL NO. NM-030991
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR BOX 68, HOBBS, N. M. 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FNL * 1980' FWL Sec 35 (Unit C, NE 1/4 NW 1/4)	8. FARM OR LEASE NAME GORMAN Federal
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3604' RDB	10. FIELD AND POOL, OR WILDCAT UNDESIGNATED
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 35-19-33 NMPM
	12. COUNTY OR PARISH LEA
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD-3484. On 6-12-68 4 1/2" OD 9.5# J-55 Casing liner was set from 2921-3483 w/ 100 sf neat. Cmc 30 sf. Tested casing w/ 1300 psi for 30 min. Test O.K. Perforated 3401, 12, 18, 23-30, 37, 42-45 w/ 25 PF, ACIDIZED w/ 6000 gal 15%. Evaluated. Perforated 3350-3400 w/ 25 PF. Acidized w/ 1000 gal 15%. Evaluated. Dry Hole. Pursuant to tele approval. Mr. Brown to EQ Snook - propose to P & A as follows: Spot cement plugs 3447-3250, 3000-1290 and 10 sf @ surface & erect P & A marker. Make final cleanup and restore ground to contour.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

044-USGS-17
1-NSW
1-SUSP
1-12R4

*See Instructions on Reverse Side

JUN 20 1968
J. L. GORDON
ACTING DISTRICT ENGINEER