

COUNTY	LEA	FIELD	Vacuum	STATE	NM 30-025-22630
OPR	MOBIL OIL CORP.			MAP	
	WI-127 Bridges-State				
	Sec. 24, T-17-S, R-34-E			CO-ORD	
	660' FSL, 560' FWL of Sec.				
	Spd 6-28-68				
	Camp 7-15-68		CLASS	EL	
	FORMATION	DATUM	FORMATION	DATUM	
CSG & SX TUBING					
8 5/8" 1605' 800					
5 1/2" 4848' 1400					
LOGS EL GR RA IND HC A					
	TD 4850'				

San Andres Perfs 4484-4785' - WATER INJECTION WELL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT Leatherwood Drlg. Co. PROP DEPTH 4900' TYPE RT
DATE

F.R. 6-27-68; WATER INJECTION WELL
PD 4900' - Grayburg-SA
Elev. 4030' GL
7-1-68 Drlg. 1628' anhy.
7-8-68 Drlg. 4717' lm.
7-15-68 TD 4850', PBD 4820', swbg.
Perf @ 4735', 4738', 4775', 4776', 4779', 4780',
4785' W/2 SPI
Perf @ 4484', 4492', 4494', 4496', 4498', 4500',
4503', 4505', 4508', 4512', 4516', 4520', 4523',
4529', 4532', 4536', 4539', 4557', 4559', W/2 SPI
Acid (4735-4785') 1000 gals (15%)
Swbd 9 BAW in 3 hrs & swbd dry (4735-85')
Acid (4484-4559') 1000 gals (15%)
Swbd 21 BLW in 1 hr & swbd dry after 2 hrs
(4484-4559')

IPA Vacuum NM Sec. 24-17S-34E
GOIL OIL CORP., #WI-127 Bridges-State Page #2

7-22-68 TD 4850', COMPLETE
LOG: Anhy 1600', Yates 2876', Queen
3801', SA 4450'.