

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Orig&3cc: OCC, Hobbs

cc: State Land Office, Santa Fe, N.M.

cc: Union Oil Co., 300 Security Nat'l
Bank Bldg., Roswell, N.M.

cc: Regional Office, cc: file

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator SINCLAIR OIL CORPORATION	5. State Oil & Gas Lease No. K 5459
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240	7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>18S</u> RANGE <u>32E</u> NMPM.	8. Farm or Lease Name State 974
	9. Well No. 1
	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

Total Depth Drilled 12,096'. Ran 13-3/8"OD 48# H-40 casing set @ 707' and cemented w/625 sxs Circulated to Surf. Ran 9-5/8"OD N-80 40# casing set @ 4430' w/1420 sxs. Circ. to surface.

PROPOSE TO: Plug and Abandon w/cement plugs set at the following intervals.

Fill hole w/heavy mud.

Spot 25 sxs cement plug @ 12,096' T.D.

Spot 25 sxs cement plug @ top of Penn @ 11,874'.

Spot 25 sxs cement plug @ top of Wolfcamp @ 9,572'.

Spot 35 sxs cement plug @ base of Bone Springs @ 8,460'.

Spot 25 sxs cement plug @ top of Delaware @ 5,500'.

Spot 25 sxs @ bottom of Intermediate @ 4,430' (9-5/8"OD casing).

Spot 10 sxs cement @ surface.

Install regulation dry hole marker, clean and level location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Tom Hembree TITLE Engineer

DATE 10-1-68

APPROVED BY [Signature] TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: