

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT ON REVERSE
(Other instructions
reverse side)TE
reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-029726

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> DRY HOLE	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION	8. FARM OR LEASE NAME DONOHUE Federal
3. ADDRESS OF OPERATOR BOX 68, HOBBS, N. M. 88240	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT UNDESIGNATED
	11. SEC., T., R., M., OR B.L.K. AND SURVEY OR AREA 26-19-33 NMPM
14. PERMIT NO.	12. COUNTY OR PARISH LEA
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3607' R.D.B.	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 6 1/8" hole to 3570' TD. No show Oil or Gas 3440- TD.
Set C I B P @ 3435 and squeezed below w/ 75 sq. cement.
Left 5' on B.P. PBD-3430, Perforated 3411-14, 18-25,
w/ 21 SPF. Acidized w/ 1000 gal 15%. Evaluated.
No show of oil or Gas. Swab 104 BW in 4 hrs. Dry Hole.
Propose to P & A as follows:
Spot 40 sq cement plug - PBD-3430- 3300'.
Cut and Pull 7" from free point - (appr 3000- 2950')
Cover salt Sec w/ 650 sq salt Sat x 4% Sol x 2% CACH
Cement - appr 2950 - 1300'. Spot 60 sq @ surface
and erect P & A marker.
Make final cleanup and restore ground to contour.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE AREA SUPERINTENDENT

DATE SEP 30 1968

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

04-4-USGS-W
1-N.S.W
1-SUSP
1-REY

*See Instructions on Reverse Side

APPROVED
OCT 3 1968
A. R. Brumby
DISTRICT ENGINEER