
DEVON ENERGY CORPORATION WELLBORE SCHEMATIC

WELL NAME: MESCALERO RIDGE UNIT "28" #32			FIELD: SOUTH QUAIL RIDGE (YATES)			
LOCATION: 660' FNL & 660' FWL, SEC 28-T19S-R34E			COUNTY: LEA			STATE: NM
ELEVATION: GL=3706'; KB=UNK			SPUD DATE: 07/18/68		COMP DATE: 10/04/68	
API#: 30-025-2276	67 PREPARED	BY: C.H. CARLETON			DATE: 01/25/02	
	DEPTH	SIZE	WEIGHT	GRADE	THREAD	HOLE SIZE
CASING:	0' - 326'	8 5/8"	20#	SP-40	ST&C	12 1/4"
CASING:	1900' - 4094'	4 1/2"	9.5#	J-55	LT&C	7 7/8"
CASING:						
TUBING:						
TUBING						



CURRENT


PROPOSED

OPERATOR: DEVON ENERGY PRODUCTION COMPANY, L.P.

CEMENT PLUG: 0'- 50' CEMENT PLUG: 275'- 375'

8 5/8" CASING @ 326' W/300 SXS. TOC @ SURFACE.

NOTE: 9.5PPG MUD TO BE SPOTTED BETWEEN CEMENT PLUGS.



CEMENT PLUG: 1800'- 1950' (TOP OF SALT @ 1900')

CUT OFF 4 1/2" CASING @ 1900'

CEMENT PLUG: 3250'- 3350' (BASE OF SALT @ 3300')



CIBP @ 3800', CAPPED WITH 35' CEMENT

PERFORATIONS: 3848'- 3854' (OA) - 14 HOLES

PBTD @ 4052'

4 1/2" CASING @ 4094' W/275 SXS. TOC @ 3000' (TEMP SURVEY)

TD @ 4100'

BUREAU OF LAWD INGMT.

82 NAL 5005

BECEINED