

COUNTY	IFA	FIELD	VACUUM	STATENM	30-025-22955
OPR	PHILLIPS PET. CO.			MAP	
	3 Mable				
	Sec 35, T-17-S, R-34-E			CO.ORD	
	2310' FNL, 990' FWL of Sec.				
	Spd 2-12-69		CLASS		EL. [REDACTED]
	Camp 4-8-69		FORMATION	DATUM	FORMATION DATUM
CSG & SX - TUBING					
8 5/8" at 367' w/200 SX					
4 1/2" at 4758' w/575 SX					
LOGS EL GR RA IND HC A					
			TD 4760'; PED 4747'		
IP (San Andres) Perf 4484-4688' P 88 BOPD + 31 BW. Pot based on 24 hr test. COR 801; Crav 36.2.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Leatherwood	PROP DEPTH	4700'	TYPE
DATE				

F.R. 1-16-69
PD 4700' (Crabburg & San Andres)
Contractor - Leatherwood

2-17-69 Drlg. 3112' achy
2-24-69 Drlg. 4595' 1m
3-4-69 TD 4760'; Prep Perf
3-11-69 TD 4760'; PED 4747'; Swbg
Perf (San Andres) 4660-68', 4678-88' w/2 SPF
Acid (4660-88') 500 gals
Swbd 1 BO + 3 BAW in 4 hrs (4660-88')
Acid (4660-88') 3000 gals
Swbd 3 BO + 41 BAW in 10 hrs (4660-88')
Perf (U. San Andres) 4484-90', 4510-24',
4530-36', 4544-82', 4562-70' w/2 SPF
Acid (4484-4570') 3500 gals
Swbd 20 BLO + 60 BAW in 7 hrs (4484-4570')

LEA

Vacuum

NM

Sec 35, T17S, R34E

PHILLIPS PET. CO.

3 Mable

Page #2

3-18-69

TD 4760'; PBD 4747'; RU Pmp

Frac (4484-4570') 40,500 gals oil + 34,500# sd

3-25-69

TD 4760'; PBD 4747'; NO Electricity

4-1-69

TD 4760'; PBD 4747'; Ppg load

Ppd 85 BIC + 36 P. 4415 wtr in 24 hrs

4-7-69

TD 4760'; PBD 4747'; Ppg load

4-14-69

TD 4760'; PBD 4747'; COMPLETE

LOG TOPS: Yates 2845', Grayburg 4015',

San Andres 4460'

4-17-69

COMPLETION REPORTED