

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy 1810'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 2046'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 3208'	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 3378'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3900'	T. Devonian	T. Menefee	T. Madison
T. Queen 4630'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 5247'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 5558'	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	1810'		Red Beds				DST - 10, 116-10, 148'
1810'	2046'		Anhy, red sand				rec. 257' oil and gas
2046'	3208'		salt w/anhy				cut salt water & 180'
3208'	3378'		Anhy				gas & water cut mud.
3378'	3900'		Red sand & anhy				60 min. preflow IFP
3900'	4630'		Anhy, dolo, red sand				41.8#, 60 min. FFP
4630'	4892'		Gray, red sand, dolo w/anhy				83.5#, 120 min. ISIP
4892'	5247'		Gray sand, dolo w/tr. anhy				1790.4#, 60 min. IFP
5247'	5558'		Dolo w/tr sand				105.4# to 146.4#, 120
5558'	5697'		Dolo				min. FSIP 1748.9#
5697'	7920'		Sand, dolo w/lm & shale				
7920'	9498'		Lm w/shale, sand & chert				
9498'	9940'		Sand, dolo & lm				
9940'	TD		Sand, lm & dolo				