

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-71424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0141013

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Me-Tex Supply Company

3. ADDRESS OF OPERATOR

Box 2070, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 1980' FNL and 1980 FEL of Sec.

7. UNIT AGREEMENT NAME

Mescalero Ridge

8. FARM OR LEASE NAME

Mescalero

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., S., M., OR BLM. AND
SURVEY OR AREA

Sec. 19, T-19-S, R-34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3699 Gr. 3709 KB

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Propose to spot a 25 sx cement plug from 3779-3910'.
2. Propose to spot a 25 sx cement plug at 4 1/2 casing stub at 2250'.
3. Propose to spot a 25 sx cement plug at top of Rustler at 1600'.
4. Propose to spot a 25 sx cement plug at 8-5/8 casing shoe at 300'.
5. Propose to spot a 10 sx cement plug at surface with marker.
6. Hole will be loaded with mud-laden fluids.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE

Agent

DATE

5/27/71

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

APPROVED

AUG 9 1971

ARTHUR R. BROWN
DISTRICT ENGINEER

RECEIVED

AUG 17 1971

OIL CONSERVATION COMM.
HOBBS, N. M.