

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

MAR 24 1970

OIL CONSERVATION COMM.

SUNDRY NOTICES AND REPORTS ON WELLS HOBBS, N. M.

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator <b>AZTEC OIL AND GAS COMPANY</b>	5. State Oil & Gas Lease No. <b>L 200</b>
3. Address of Operator <b>P. O. BOX 837 HOBBS, NEW MEXICO 88240</b>	7. Unit Agreement Name
4. Location of Well UNIT LETTER <b>J</b> <b>1980</b> FEET FROM THE <b>SOUTH</b> LINE AND <b>1980</b> FEET FROM THE <b>EAST</b> LINE, SECTION <b>24</b> TOWNSHIP <b>17S</b> RANGE <b>36E</b> N14MPM.	8. Farm or Lease Name <b>STATE DS</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3801 EL</b>	9. Well No. <b>3</b>
	10. Field and Pool, or Wildcat <b>WILDCAT</b>
	12. County <b>LEA</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled 4 3/4" hole from 5051' to 6794'. Set 3 1/2" OD Hydrill Liner from 4985' to 6794', 59 joints, cement with 175 sacks Encor. Plug down at 12:05 A.M. Ran temperature survey, found top of cement at 5050'. Pressure test liner would not hold. Squeeze top of liner with 150 sacks Encor at 1,000 PSI. Shut in 14 hours, pressure test to 1,000 PSI for 30 minutes.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Henry Thompson* TITLE FIELD FOREMAN DATE 3-23-70  
APPROVED BY *[Signature]* TITLE SUPERVISOR DISTRICT DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

THE  
MOUNTAIN  
VIEW  
CAMP