

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDY NOTICES AND REPORTS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR RE-DRILL A WELL OR TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR RE-ENTRY" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. B-1520
1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Injection	7. Unit Agreement Name	
2. Name of Operator Mobil Oil Corporation	8. Farm or Lease Name N. Vacuum Abo Unit	
3. Address of Operator Box 633, Midland, Texas 79701	9. Well No. 130	
4. Location of Well UNIT LETTER H , 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 15 TOWNSHIP 17-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat North Vacuum Abo	
11. Elevation (Show whether DF, RT, GR, etc.) 4052.9 GR	12. County Lea	

Check Appropriate Box To Indicate
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

13. Date of Notice, Report or Other Data
SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Convert to Abo WIW 12,612 TD
Schl capped DR plug w/7x 35' of cmt 11,978-11,943, then set Baker 7" CIBP @ 8750, LD 102 jts of 2-3/8 tbg. then ran 2-3/8 Knox Serv Co spotted 300 gals 15% iron stabilized acid @ 8747, POH, Schl perf 7" csg in the Abo @ 8678,79,91,92,93,8701,02,03,05,06,07,09,10 & 8711 w/2-JSPF, total of 28 holes, ran Baker 7" FB pkr on 2-3/8 tbg set @ 8585, Knox acidized perfs w/5000 gals 15% iron stabilized acid, used 45 RCNBS flushed & overflushed w/15,000 gals TFW, TTP 3800-4400, AIR 4.2 BPM, ISIP 3500, 10 min 3400 Finish running 2-3/8 tbg OE to 8643, SN w/1.81 ID @ 8636, 6'x2-3/8 sub 8630-36; 6' x 4 1/2 mill out ext 8624-30, Baker 7" Model NB pkr set @ 8621 w/Model D seal assembly, 291 jts 2-3/8 N80 Buttress tbg tested to 7000# while running loaded csg w/TFW, set pkr w/8000# wt, inst'l inj head, Started injection 1-4-74

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine O. Tucker TITLE Proration Clerk DATE 1-15-74

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: