

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-199
7. Unit Agreement Name
8. Farm or Lease Name STATE "SS"
9. Well No. 2
10. Field and Pool, or Wildcat Spencer-S.A.
12. County Lea

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. CIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER- WELL <input type="checkbox"/>
2. Name of Operator AZTEC OIL & GAS COMPANY
3. Address of Operator P. O. Box 837, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER G 2310 FEET FROM THE North LINE AND 1980 FEET FROM East 24 LINE, SECTION 17-S RANGE 36-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3810 DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Deepen

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A 4-3/4" hole was drilled from 5050' to 5335'. Lost circulation, could not regain. Left one 3 1/2" Drill Collar, one 4-3/4" Reamer and one 4-3/4 Bit in hole. Squeezed open hole with 100 sacks Class "C" and 100# Mini Beads to 2000 psi. Set C.I.B.P at 4966'. Reperforated at 4952-58'. Put back on Pump.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

original signed by
LESTER L. DUKE

District Superintendent

April 2, 1973

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

TITLE

DATE