

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-8165	
7. Unit Agreement Name	
-	
8. Farm or Lease Name	
Consolidated-State	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Undesignated	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Consolidated Oil & Gas, Inc.
3. Address of Operator
Suite 1300 - 1860 Lincoln St., Denver, Colorado 80203
4. Location of Well
UNIT LETTER <u>L</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>17S</u> RANGE <u>37E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3766.9 G. L.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 356'. Ran 11 joints of 8-5/8" o.d. 8rd. 24 & 32# set at 355' K. B. Cemented with 250 sacks Class "C" plus 3% CaCl. Plug down at 11:00 a.m. 5/24/70. Good cement returns to surface. Waited on cement 18 hrs. Pressure tested surface casing to 1,000 psi for 30 min. -- held O. K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Vernon J. Lowe TITLE Drilling Superintendent DATE 5/25/70  
APPROVED BY Leslie J. Clement TITLE Oil & Gas Inspector DATE JUN 1 1970  
CONDITIONS OF APPROVAL, IF ANY:

**RECEIVED**

**MAY 28 1970**

**OIL CONSERVATION COMM.  
HOBBS, N. M.**