

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1520

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Mobil Oil Corporation	8. Farm or Lease Name Bridges State
3. Address of Operator P. O. Box 633, Midland, Texas 79701	9. Well No. 138
4. Location of Well UNIT LETTER L, 1980 FEET FROM THE South LINE AND 860 FEET FROM THE West LINE, SECTION 26 TOWNSHIP 17-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4024.3 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/12 (1) 1615 ND anhy, 12 1/4" hole, 1" @ 1615. S. Mud.
Marcum Drlg Co spud in @ 9:00 a.m. 7/11/70, ran 40 jts
1615' 8-5/8 OD 23.0# J-55 8rd ST&C csg cemented on bottom
@ 1615 by Howco w/ 1000x Class H cement w/ 8% gel + 2%
CaCl + 200x Incor Neat cement w/ 2% CaCl, PD 7:45 a.m.
7/12/70, cement circ.

7/13 (2) 2165 drlg salt, 7-7/8" hole, 3/4 @ 1920, Br Wtr.
WOC total 18 hrs, test csg and BOP's 800#/ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Authorized Agent DATE 7/15/70
APPROVED BY [Signature: Leslie A. Clements] TITLE Oil & Gas Inspector DATE JUL 17 1970
CONDITIONS OF APPROVAL, IF ANY: