NO. OF COPIES PECCEVED			Supersedes Old
DISTRIBUTION			C-102 and C-103
SANTAFE	NEW MEX	ICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE			Sa. Indicute Type of Lease
U.S.G.S.	4		Stote X Fee
LAND OFFICE	4-1		5, State Off & Gua Leave No.
OPERATOR	لــــــــــــــــــــــــــــــــــــــ		B-1520
		ACROST COLLUCT LE	THE STREET STREET
IDD NOT USE THIS FORM F	UNDRY NOTICES AND R	REPORTS ON WELLS Fundan Calmida EACH TO A DIFFERENT RESERVE A CONCLEGE WITH PACKAGOLS.)	7. Unit Agreenced Finance
OIL X WELL WELL	DTHER-		6, Farm or Lease Name
Mobil Producing TX. & N.M. Inc.			North Vacuum Abo Unit
3. Address of Operator			9. Well No.
Nine Greenway Plaza	, Suite 2700, Houst	ton, Texas 77046	203
4. Lecation of Well			
UNIT LETTER B 1780 FEET FROM THE EAST LINE AND 660 FEET FROM			- FEET FROM North Vacuum-Abo
Nameh 22 17 C 2/ E			
North LINE, SECTION 22 TOWNSHIP 17-S RANGE 34-E HMPP			
manatal and the same	TTTTTTT ELECTION	on (Show whether DF, RT, GR, etc.)	12. County
	//////////	49 GR	Lea
	ieck Appropriate Box T of intention to:	o Indicate Nature of Notice, Rep 1 sue	SEQUENT REPORT OF:
ROTTOL			·
PERFORM REMEDIAL WORK	PLUG A	ND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABLIDONMENT
PULL OR ALTER CASING	CHANGE	PLANS CASING TEST AND CEMENT .	708
-		OTHER	
DTHER		U .	
17 Describe Proposed of Comple	eted Operations (Clearly state	all pertinent details, and give pertinent details	es, including estimated date of starting any proposed
work) SEE RULE 1103.			
(1) POOH w/rods, pu	ump and tubing.		
(2) GIH w/RBP and s	set at 2740', cap w:		
			ed at 2640 (from temperature
survey).	_		
		te $w/6$ shots at the top of t	
(5) Bleed down any	pressure, then GIH	w/cmt retainer, set 50' abo	ove peris.
(6) Establish circu	ilation behind 5½ ca	asing to surtace by pumping	a fluid caliper (dye) w/water.
	SUU SX OI CLASS "C"	w/2% carcium cnioride, circ	culate to surface and squeeze
to 300 psi.	mine if coment cot		
(8) POOH and determine if cement set.(9) If cement did not circulate run a temperature survey to find the top of the cement and			
evaluate.	ior circulate iun a	rembetarare sarvey to time	the top of the cement and
(10)GIH and drill of	out cement plug.		
, ,	to 1000 psi, do not	exceed 1000 psi.	
	off of RBP and ret		
(13)GIH w/rods, pun			
	and return to produ	uction.	
·			
		state to the heat of my knowledge and belief.	
18. I hereby certify that the infor	unation whose is time and coul	plete to the best of my knowledge and belief.	
Pullie C	Jaix	Authorized Agent	DAYE 4/11/80
BILL CONTRACTOR CONTRACTOR	J		
Or	rig. Signed by		APR 12 1980
APPROVED BY	Sexton	TITLE	DATE
_	1 SHUTE		