

WELL WORK RECOMMENDATIONS
Proposals for Well Reconditioning and Subsurface Maintenance
Workovers, Expense DD's, PB's, and Conversions

Case: NORTH VERMONT ABO UNIT Well No. 151
Field: NORTH VERMONT (ABO)
County: LIER State: NEW MEXICO

RECOMMENDED PROCEDURE:

OF CORTON 2207 / 1,000 GALS OF WATER. SET THE
PACKER APPROXIMATELY 50' ABOVE THE INJECTION INTERVAL.

7. PUT THE WELL ON INJECTION.

NOTE: IF HIGH PRESSURE ALTERNATE GAS AND WATER
INJECTION PROTECTION IS PLANNED.

ILLEGIBLE

D.D. COMMERCIAL WELL SURV. 1
NORTH VACCOON No. 121
NORTH VACCOON (NO.) FIELD
LEWIS COUNTY, MISSISSIPPI

ILLEGIBLE

C.L. ELEV = 4030'
ELEV =

3/8" - 48.54 #61 #/FL. J-55 H-40
SET W/ 1475 SX. CIRC.

CMT. TOP (T.S.)

350'

780'

LINER TOP

4,259'

5/8" - 40 #/FL. S-95 SET W/ 12900 SX
MIN. BURST PRESS. = 3330

5,050'

BAKER MOD. 'D' PKR.
W/ LATCH IN ASSY.

2 3/8" N-80 EUE SRD. TBG Z
11800'

11,765'

MORROW PERFORATIONS
11,353' - 11,381' - 28' OA - 15 HOLES

7" - 26 #/FL. S-95 SET W/ 11700 SX
MIN. BURST PRESS. = 3870

4-16-73.

ICW

12,178'

12,180' T.D.