

Form 5-421
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE CATEGORY
(Other instructions on reverse side)Form approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth. Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

1. NAME OF OPERATOR

Inexco Oil Company

2. ADDRESS OF OPERATOR

c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N.M.

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

660' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, CR, etc.)

U.K.

4. LEASE DESIGNATION AND SERIAL NO.

LC-029416

5. IF INDIAN, ALLOTTEE OR TRIBE NAME

6. UNIT AGREEMENT NAME

7. FARM OR LEASE NAME

Jewett McDonald Fed.

8. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., NE, OR SE, AND SURVEY OF AREA

15-18S-32E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Propose to spot a 25 sx cement plug at 8-5/8 casing shoe at 4425'.
2. Propose to spot a 25 sx cement plug at 8-5/8 casing stub at 3000'.
3. Propose to spot a 25 sx cement plug at 13-3/8 casing shoe at 610'.
4. Propose to spot a 10 sx cement plug at surface with marker.
5. Hole will be loaded with mud-laden fluids.

REMARKS: If 8-5/8" casing is pulled from below 1,250 feet, place additional 25 sack cement plug at 1,150-1,250 feet.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

6/30/71

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED
JUL 6 1971ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED

JUL 13 1971

OIL CONSERVATION COMM.
HOBBES, W. M.